





LOGIC FI A

213 47 112 A

AVAILABLE IN
ALU GREY 213 47 112 A



 [View on website](#)



General info

LOCATION	outdoor
INSTALLATION	Floor Recessed
CUTOUT SHAPE/SIZE (MM)	round - 93
RECESSED DEPTH (MM)	40
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	0.2
ADJUSTABILITY	non adjustable
INFORMATION	EXCL.LED POWER SUPPLY 24V-DC max.600kg

Electrical info

ELECTRICAL	24V-DC
CLASS	III
DIM TYPE	non-dimmable
ENERGY CLASS	G
CERTIFICATES	CB, EAC, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED 0,6W / CRI>80 / 3000K / 45lm
LED TECHNICS (LIGHT SOURCE)	45lm // 0,6W // 75lm/W
LED TECHNICS (LUMINAIRE)	3lm // 1W // 5lm/W

Requirements

LED POWER SUPPLY 24V-DC

Options

GENIE BOX 90 R
CBOX

LOGIC F1 A


213 47 112 A

For detailed installation instructions, please consult the manual: [213_47_112_HAND.pdf](#)

FINISH YOUR SPECIFICATION


LED power supplies

#



300 89 24 150 LED POWER SUPPLY 24V-DC / 150W


250



21012 0160 LED POWER SUPPLY 24V-DC / 24W


40

Ground mounting boxes



213 19 09 LOGIC 90 BOX R

Waterproof connection parts



216 12 00 CBOX

Notes: