





LOGIC F2 A
213 47 122 A

AVAILABLE IN
ALU GREY 213 47 122 A



 [View on website](#)



General info	
LOCATION	outdoor
INSTALLATION	Floor Recessed
CUTOUT SHAPE/SIZE (MM)	round - 93
RECESSED DEPTH (MM)	40
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	0.2
ADJUSTABILITY	non adjustable
INFORMATION	EXCL.LED POWER SUPPLY 24V-DC max.600kg

Electrical info	
ELECTRICAL	24V-DC
CLASS	III
DIM TYPE	non-dimmable
ENERGY CLASS	G
CERTIFICATES	CB, EAC, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED 0,6W / CRI>80 / 3000K / 45lm)
LED TECHNICS (LIGHT SOURCE)	90lm // 1,2W // 75lm/W
LED TECHNICS (LUMINAIRE)	7lm // 1W // 5lm/W

Requirements	
LED POWER SUPPLY 24V-DC	

Options	
GENIE BOX 90 R	
CBOX	


LOGIC F2 A

213 47 122 A

For detailed installation instructions, please consult the manual: [213_47_112_HAND.pdf](#)


FINISH YOUR SPECIFICATION

LED power supplies #



300 89 24 150 LED POWER SUPPLY 24V-DC / 150W


125 ☐



21012 0160 LED POWER SUPPLY 24V-DC / 24W

20 ☐


Ground mounting boxes



213 19 09 LOGIC 90 BOX R

☐

Waterproof connection parts



216 12 00 CBOX

☐

Notes: