





BAZIL 121 A-ANO

222 121 12 A-ANO

AVAILABLE IN
ALU GREY-ALU ANODIZED 222 121 12 A-ANO
ANTHRACITE (DARK GREY)-ALU ANODIZED 222 121 12 N-ANO



[View on website](#)

General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted
INGRESS PROTECTION	IP55
PROTECTION AGAINST MECHANICAL IMPACT	IK08
WEIGHT (KG)	2.9
ADJUSTABILITY	non adjustable
INFORMATION	INCL.LED POWER SUPPLY 500mA-DC

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 9,8W / CRI>80 (R9: 50) / 3000K / 1348lm
SDCM	SDCM5
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	1348lm // 9,8W // 138lm/W
LED TECHNICS (LUMINAIRE)	1128lm // 11W // 100lm/W

Options	
PIN 3	
CBOX	
IP68 CONNECTION KIT	
IP68 CONNECTOR 3P	


For detailed installation instructions, please consult the manual: [222_121_12_HAND.pdf](#)

BAZIL 121 A-ANO

222 121 12 A-ANO


FINISH YOUR SPECIFICATION

Waterproof connection parts



216 12 00 CBOX

☐



216 12 01 IP68 CONNECTION KIT


☐



216 12 02 IP68 CONNECTOR 3P

☐

Pins and plates for bollards



229 01 03 PIN 3

☐

Notes: