



BOXY R 92733 B-B

251 70 811 922 B-B

AVAILABLE IN



BLACK-BLACK 251 70 811 922 B-B

BLACK-FLEMISH BRONZE 251 70 811 922 B-FBR

BLACK-FLEMISH GOLD 251 70 811 922 B-FG

WHITE-BLACK 251 70 811 922 W-B

WHITE-WHITE 251 70 811 922 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.6
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-33° INCL.LED POWER SUPPLY 500mA-DC

Electrical info

ELECTRICAL	110-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUPE	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	815lm // 10W // 82lm/W

Options

COVERSET R 100

Accessories

BOXY HONEYCOMB
BOXY SOFTENING LENS
BOXY GLASS SBL


BOXY R 92733 B-B

251 70 811 922 B-B

For detailed installation instructions, please consult the manual: [251 70 811 XXX HAND.pdf](#)

FINISH YOUR SPECIFICATION

Coversets



204 00 100 B COVERSET R 100 B

☐

204 00 100 W COVERSET R 100 W

☐

Light altering devices



251 70 03 01 B BOXY HONEYCOMB B

☐

251 70 03 01 W BOXY HONEYCOMB W

☐

251 70 03 04 B BOXY SOFTENING LENS B

☐

251 70 03 04 W BOXY SOFTENING LENS W

☐

251 70 03 05 B BOXY GLASS SBL B

☐

251 70 03 05 W BOXY GLASS SBL W

☐



BOXY R 92733 B-B

251 70 811 922 B-B

Notes: