





## LOGIC 60 R MOON 93020 ANO

213 45 10 811 932 ANO

AVAILABLE IN

**ALU ANODIZED** 213 45 10 811 932 ANO



[View on website](#)



### General info

|                                             |                                                                                                                                                                      |
|---------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>LOCATION</b>                             | outdoor                                                                                                                                                              |
| <b>INSTALLATION</b>                         | Floor Recessed                                                                                                                                                       |
| <b>CUTOUT SHAPE/SIZE (MM)</b>               | round - 61                                                                                                                                                           |
| <b>RECESSED DEPTH (MM)</b>                  | 100                                                                                                                                                                  |
| <b>INGRESS PROTECTION</b>                   | IP67                                                                                                                                                                 |
| <b>PROTECTION AGAINST MECHANICAL IMPACT</b> | IK08                                                                                                                                                                 |
| <b>WEIGHT (KG)</b>                          | 0.5                                                                                                                                                                  |
| <b>ADJUSTABILITY</b>                        | non adjustable                                                                                                                                                       |
| <b>INFORMATION</b>                          | REFLECTOR FL-20°<br>INCL.1 x CABLE H05 RN-F 2 x 1mm <sup>2</sup> 0,5m<br>EXCL.LED POWER SUPPLY 350mA-DC<br>IEC 60598-2-13 : max.150kg 25N/cm <sup>2</sup><br>ESG 5mm |

### Electrical info

|                     |                           |
|---------------------|---------------------------|
| <b>CLASS</b>        | III                       |
| <b>DIM TYPE</b>     | depending on power supply |
| <b>ENERGY CLASS</b> | D                         |
| <b>CERTIFICATES</b> | CB, EAC, ENEC             |

### Lightsource info

|                                    |                                                  |
|------------------------------------|--------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                              |
| <b>LIGHTSOURCE</b>                 | LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm |
| <b>TM-30 VALUES</b>                | rf: 90 / Rg: 99                                  |
| <b>SDCM</b>                        | SDCM1                                            |
| <b>RISKGROUP</b>                   | RG1                                              |
| <b>LM80</b>                        | L90B10 > 50000                                   |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 787lm // 5,8W // 135lm/W                         |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 353lm // 7W // 53lm/W                            |

### Requirements

LED POWER SUPPLY 350mA-DC DIM

## LOGIC 60 R MOON 93020 ANO

213 45 10 811 932 ANO

### Options

---

LOGIC 60 BOX R

CBOX

IP68 CONNECTION KIT

IP68 CONNECTOR 3P

For detailed installation instructions, please consult the manual: [213\\_45\\_10\\_811\\_XXX\\_HAND.pdf](#)


# LOGIC 60 R MOON 93020 ANO

213 45 10 811 932 ANO

## FINISH YOUR SPECIFICATION

### LED power supplies


#



**300 90 63**

LED POWER SUPPLY MULTI-POWER DIM9


1->4(4)

☐


**300 90 68**

LED POWER SUPPLY MULTI-POWER DIM5


1->2(1)

☐


**300 90 69**

LED POWER SUPPLY MULTI-POWER HV DIM9


2->6(6)

☐


**300 90 124**

LED POWER SUPPLY MULTI-POWER DIM7


2(2)

☐


**300 90 125**

LED POWER SUPPLY MULTI-POWER MINI DIM5


2(2)

☐


**21012 0010**

LED POWER SUPPLY MULTI POWER


1->2

☐


**21012 0021**

LED POWER SUPPLY MULTI POWER DIM1


1->2

☐


**21012 0035**

LED POWER SUPPLY MULTI POWER DIM5

1->2

☐


**21012 005W**


LED POWER SUPPLY MULTI-POWER COMPACT WDL

1->2

☐

LOGIC 60 R MOON 93020 ANO

213 45 10 811 932 ANO




23  
122  
41

**21012 0258** LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8

1

☐




140  
26  
38

**21012 0298** LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

1->2

☐




54  
26  
122

**21012 0480** LED POWER SUPPLY 350mA-DC / 17W IP68

1-2(2)

☐




22  
171  
90

**21032 0295** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

1

☐

Ground mounting boxes



Ø70  
52  
100  
48  
170  
120




**213 19 10** LOGIC 60 BOX R

☐



# LOGIC 60 R MOON 93020 ANO

213 45 10 811 932 ANO

| Waterproof connection parts                                                       |                                      | #                          |
|-----------------------------------------------------------------------------------|--------------------------------------|----------------------------|
|   | <b>216 12 00</b> CBOX                | <input type="checkbox"/>   |
|   | <b>216 12 01</b> IP68 CONNECTION KIT | <input type="checkbox"/>   |
|  | <b>216 12 02</b> IP68 CONNECTOR 3P   | <input type="checkbox"/>   |
|  | <b>216 14 35</b> CBOX 350 mA / 10W   | 1 <input type="checkbox"/> |

Notes: