





LOGIC 90 R WALLWASH 930 ANO

213 473 811 930 ANO

AVAILABLE IN
ALU ANODIZED 213 473 811 930 ANO



[View on website](#)



General info

LOCATION	outdoor
INSTALLATION	Floor Recessed
CUTOUT SHAPE/SIZE (MM)	round - 93
RECESSED DEPTH (MM)	125
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK07
WEIGHT (KG)	1
ADJUSTABILITY	non adjustable
INFORMATION	INCL.CABLE H05 RN-F 2 x 1mm ² 0,5m INCL.LED POWER SUPPLY 350mA-DC INCL.IP68 CONNECTOR 3P IEC 60598-2-13 : max.150kg 25N/cm ² ESG 5mm

Electrical info

ELECTRICAL	100-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	787lm // 5,8W // 135lm/W
LED TECHNICS (LUMINAIRE)	488lm // 7W // 73lm/W

Options

LOGIC 90 BOX R
CBOX


LOGIC 90 R WALLWASH 930 ANO

213 473 811 930 ANO

For detailed installation instructions, please consult the manual: [213_473_811_XXX_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Ground mounting boxes




213 19 09

 LOGIC 90 BOX R

☐

Waterproof connection parts



216 12 00

 CBOX

☐

Notes: