




M20/M26H - TWEETER BL 930 MDL B

421 522 811 930 MDL B

AVAILABLE IN

BLACK 421 522 811 930 MDL B


WHITE 421 522 811 930 MDL W



Ø147



0-45°
355°



 [View on website](#)

General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° to 45° swiveling, 355° rotatable
INFORMATION	EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	E
CERTIFICATES	EAC, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1089lm // 8,6W // 127lm/W
LED TECHNICS (LUMINAIRE)	1067lm // 10W // 108lm/W

Remarks

Take a look at our **MAGNETIC PROFILES** movie

Requirements

BOWL GLASS CLEAR
BOWL GLASS AMBER
BOWL GLASS OPAL WHITE
LED POWER SUPPLY 48V-DC

M20/M26H - TWEETER BL 930 MDL B

421 522 811 930 MDL B

Options

DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual: [421_522_811_XXX_MDL_HAND.pdf](#)

M20/M26H - TWEETER BL 930 MDL B

421 522 811 930 MDL B

FINISH YOUR SPECIFICATION

Current supply

#



21032 0030 SMART 48 MODULATOR PLUG-IN WD

16


SMART 48

#



300 90 011 SMART 48 MODULATOR DIM9

16



300 90 012 SMART 48 MODULATOR WD

16

LED power supplies

#



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

8



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

20



21012 0230 LED POWER SUPPLY 48V-DC / 100W

8




21012 0240 LED POWER SUPPLY 48V-DC / 200W

16


M20/M26H - TWEETER BL 930 MDL B

421 522 811 930 MDL B


To be used with ...



286 67 01 BOWL GLASS CLEAR



286 67 02 BOWL GLASS AMBER



286 67 03 BOWL GLASS OPAL WHITE


M20/M26H - TWEETER BL 930 MDL B

421 522 811 930 MDL B


COMPATIBLE COMPOSABLES

SHIFTLINE M26H profile


Available Colours




23359 0000 SLM26H - PROFILE



23359 0010 SLM26H - PROFILE 1m



23359 0020 SLM26H - PROFILE 2m



23359 0030 SLM26H - PROFILE 3m



SPLITLINE M20 ST profile

Available Colours



23397 0000 SPM20 ST - PROFILE



23397 0020 SPM20 ST - PROFILE 2m



23397 0030 SPM20 ST - PROFILE 3m




M20/M26H - TWEETER BL 930 MDL B


421 522 811 930 MDL B

SPLITLINE M20 profile


Available Colours




420 20 10 00 SPM20 - PROFILE 1m



420 20 20 00 SPM20 - PROFILE 2m



420 20 30 00 SPM20 - PROFILE 3m



23301 0000 SPM20 - PROFILE B



Notes: