





M52 - 1 LED D 92733 MDL

421 228 811 922 D MDL



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-33° EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	D
CERTIFICATES	CB, EAC, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	753lm // 5,8W // 129lm/W
LED TECHNICS (LUMINAIRE)	437lm // 7W // 66lm/W

Requirements

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

 DELTALIGHT®

M52 - 1 LED D 92733 MDL

421 228 811 922 D MDL

For detailed installation instructions, please consult the manual: [421_228_811_XXX_D_MDL_HAND.pdf](#)

M52 - 1 LED D 92733 MDL

421 228 811 922 D MDL

FINISH YOUR SPECIFICATION

Current supply

#




21032 0030 SMART 48 MODULATOR PLUG-IN WD

23


SMART 48

#



300 90 011 SMART 48 MODULATOR DIM9

23




300 90 012 SMART 48 MODULATOR WD

23


LED power supplies

#




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

12




300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

29



21012 0230 LED POWER SUPPLY 48V-DC / 100W

12



21012 0240 LED POWER SUPPLY 48V-DC / 200W

24


M52 - 1 LED D 92733 MDL

421 228 811 922 D MDL


COMPATIBLE COMPOSABLES

SPLITLINE M52 profile


Available Colours




420 52 10 00 SPM52 - PROFILE 1m



420 52 20 00 SPM52 - PROFILE 2m



420 52 30 00 SPM52 - PROFILE 3m



24413 0000 SPM52 - PROFILE



Notes: