





SPY C 92733 DIM8 B

279 776 811 922 ED8 B

AVAILABLE IN
BLACK 279 776 811 922 ED8 B
WHITE 279 776 811 922 ED8 W



 [View on website](#)

General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.8
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-33° INCL.DIMMABLE LED POWER SUPPLY 350mA-DC INCL.1 x CABLE SUSPENSION SINGLE AUTO. 1.6m INCL.1 x CABLE 2 x 0.75mm ²

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	D
CERTIFICATES	CB, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	753lm // 5,8W // 129lm/W
LED TECHNICS (LUMINAIRE)	387lm // 7W // 58lm/W

Requirements	
SPY TUBE	

Options	
SUSPENSION + CONNECTION TRIMLESS	

SPY C 92733 DIM8 B

279 776 811 922 ED8 B

Accessories

HONEYCOMB 50

LINEAR SPREAD LENS 50

SPREAD LENS 50

SOFTENING LENS 50


GLASS SBL 50

For detailed installation instructions, please consult the manual: [279_776_811_XXX_ED8_HAND.pdf](#)

SPY C 92733 DIM8 B
279 776 811 922 ED8 B

FINISH YOUR SPECIFICATION


Miscellaneous control equipment



300 90 004 ED8 WIRELESS CONTROL DIM8

☐

Suspension parts



328 10 02 SUSPENSION + CONNECTION TRIMLESS O.F.A.


☐

Light altering devices




413 03 01 B HONEYCOMB 50 B

☐




413 03 02 LINEAR SPREAD LENS 50

☐



413 03 03 SPREAD LENS 50

☐



413 03 04 SOFTENING LENS 50

☐



413 03 05 GLASS SBL 50

☐

Finish your product

	53 414 01 00 B SPY TUBE B	☐
	414 01 00 FBR SPY TUBE FBR	☐
	414 01 00 FG SPY TUBE FG	☐
	414 01 00 W SPY TUBE W	☐

Notes: