



SUPERNOVA LINE TRIMLESS 65 TW DIM5

274 89 06 26 ED5



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 685
RECESSED DEPTH (MM)	200
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	6.6
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL INCL.DIMMABLE LED POWER SUPPLY - DALI (DT6) 2 DALI CONTROL CHANNELS

Electrical info

ELECTRICAL	120-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	F
CERTIFICATES	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	@ 2700K: LED cluster 45W / CRI>80 / 2700K - 5700K / 4208lm Or @ 5700K: LED cluster 45W / CRI>80 / 2700K - 5700K / 4841lm
LED TECHNICS (LIGHT SOURCE)	@ 2700K: 4208 lm // 45 W // 94 lm/W Or @ 5700K: 4841 lm // 45 W // 108 lm/W
LED TECHNICS (LUMINAIRE)	@ 2700K: 3131lm // 52W // 60lm/W Or @ 5700K: 3592lm // 52W // 69lm/W

For detailed installation instructions, please consult the manual: [274_89_06_XX_ED5_HAND.pdf](#)

SUPERNOVA LINE TRIMLESS 65 TW DIM5


274 89 06 26 ED5

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
	System ceiling -
	Plasterboard -

FINISH YOUR SPECIFICATION

Miscellaneous control equipment



300 90 004 ED5 WIRELESS CONTROL DIM5

☐

Notes: