



TIGA LED 92724 DIM8 A

223 751 811 922 ED8 A

AVAILABLE IN



ALU GREY 223 751 811 922 ED8 A

BLACK 223 751 811 922 ED8 B

FLEMISH BRONZE OUTDOOR 223 751 811 922 ED8 FBRX

ANTHRACITE (DARK GREY) 223 751 811 922 ED8 N

WHITE 223 751 811 922 ED8 W



[View on website](#)



General info

LOCATION	indoor-outdoor
INSTALLATION	Wall Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK06
WEIGHT (KG)	1.4
ADJUSTABILITY	non adjustable
INFORMATION	2 x REFLECTOR 24° INCL.DIMMABLE LED POWER SUPPLY 350mA-DC

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	D

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	753lm // 5,8W // 129lm/W
LED TECHNICS (LUMINAIRE)	491lm // 7W // 74lm/W


For detailed installation instructions, please consult the manual: [223 751 811_XXX_ED8_HAND.pdf](#)

TIGA LED 92724 DIM8 A

223 751 811 922 ED8 A

FINISH YOUR SPECIFICATION

Miscellaneous control equipment



300 90 004 ED8 WIRELESS CONTROL DIM8

☐

Notes: