




TWEETER M ON 1 92750 DIM8 B-C

418 51 811 923 ED8 B-C

AVAILABLE IN
BLACK-CHROMED 418 51 811 923 ED8 B-C
WHITE-WHITE 418 51 811 923 ED8 W-W



 [View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted,Wall Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.8
ADJUSTABILITY	0° to 45° swiveling, 355° rotatable
INFORMATION	REFLECTOR WFL-50° INCL.DIMMABLE LED POWER SUPPLY 500mA-DC

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	798lm // 10W // 81lm/W


For detailed installation instructions, please consult the manual: [418_51_811_XXX_HAND.pdf](#)

TWEETER M ON 1 92750 DIM8 B-C

418 51 811 923 ED8 B-C

FINISH YOUR SPECIFICATION

Miscellaneous control equipment



300 90 004 ED8 WIRELESS CONTROL DIM8

☐

Notes: