





TWEETER M TRIMLESS 92750 W-W

418 11 811 923 W-W

AVAILABLE IN
BLACK-CHROMED 418 11 811 923 B-C
WHITE-WHITE 418 11 811 923 W-W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - Ø KIT
RECESSED DEPTH (MM)	80
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 45° swiveling, 355° rotatable
INFORMATION	REFLECTOR WFL-50° EXCL.LED POWER SUPPLY 350-500mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8-8,6W / CRI>90 (R9: 60) / 2700K / 753-1041lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	798lm // 10W // 81lm/W

Requirements

MOUNTING KIT R102 TRIMLESS O.F.A.
LED POWER SUPPLY 350 / 500mA-DC DIM (Remote)

For detailed installation instructions, please consult the manual: [418_11_811_XXX_HAND.pdf](#)

TWEETER M TRIMLESS 92750 W-W

418 11 811 923 W-W










CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 System ceiling	 MOUNTING KIT R102 TRIMLESS O.F.A.	Required
 Plasterboard	 MOUNTING KIT R102 TRIMLESS O.F.A.	Required
 Stucanet	 MOUNTING KIT R102 TRIMLESS O.F.A.	Required
 Concrete + plaster	 MOUNTING KIT R102 TRIMLESS O.F.A.	Required
 Lintel + plaster	 MOUNTING KIT R102 TRIMLESS O.F.A.	Required
 Hollow-core slab + plaster	 MOUNTING KIT R102 TRIMLESS O.F.A.	Required
 Stretched ceiling	 MOUNTING KIT R102 TRIMLESS CSC	Required
	 MOUNTING KIT R102 TRIMLESS WSC	Required

TWEETER M TRIMLESS 92750 W-W


418 11 811 923 W-W

FINISH YOUR SPECIFICATION

LED power supplies			#
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9	1->4(4) / 1->4(4)	☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5	1->2(1) / 1->2(1)	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9	2->6(6) / 1->6(4)	☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7	1->2(1) / 1(1)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5	1->2(1) / 1(1)	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL	1->2 / 1->2	☐
	21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8	1	☐
	21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8	1	☐
	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8	2->2	☐


TWEETER M TRIMLESS 92750 W-W

418 11 811 923 W-W




21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

1->2 / 1->2




21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68

1-2(2)




21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68

1-2(1)



21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

1




21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

1




Mounting kits



15212 2010 MOUNTING KIT R102 TRIMLESS O.F.A.



Mounting kits stretched ceiling



15212 0090 MOUNTING KIT R102 TRIMLESS CSC



15212 0170 MOUNTING KIT R102 TRIMLESS WSC





TWEETER M TRIMLESS 92750 W-W

418 11 811 923 W-W

Notes: