





DOT.COM L2 ON 92716 DIM8 B-B
424 113 02 921 ED8 B-B

AVAILABLE IN
BLACK-BLACK 424 113 02 921 ED8 B-B
WHITE-BLACK 424 113 02 921 ED8 W-B



General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.7
ADJUSTABILITY	non adjustable
INFORMATION	2 x REFLECTOR SP-16° INCL.DIMMABLE LED POWER SUPPLY 700mA-DC
Electrical info	
ELECTRICAL	230V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	E
CERTIFICATES	CB, EAC, ENEC, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 4,1W / CRI>90 (R9: 50) / 2700K / 425lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	425lm // 4,1W // 104lm/W
LED TECHNICS (LUMINAIRE)	331lm // 5W // 70lm/W

For detailed installation instructions, please consult the manual: [424_113_02_XXX_HAND.pdf](#)



DOT.COM L2 ON 92716 DIM8 B-B

424 113 02 921 ED8 B-B

Notes: