





XY180 S121 PUNK B

422 162 811 932 B

AVAILABLE IN
BLACK 422 162 811 932 B



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.6
ADJUSTABILITY	0° to 120° swiveling, 360° rotatable
INFORMATION	Spot : REFLECTOR FL-33° INCLLED POWER SUPPLY 350mA-DC CABLING 1 CIRCUIT

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	Tube: LED flex 8,9W / CRI>90 / 3000K / 1050lm Spot: LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
TM-30 VALUES	Spot: rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	Tube: 1050lm // 8,9W // 118lm/W Spot: 787lm // 5,8W // 135lm/W
LED TECHNICS (LUMINAIRE)	Tube: 874lm // 10W // 85lm/W Spot: 405lm // 7W // 61lm/W

Remarks

[Look at the XY180 brochure](#)

Requirements

SPY TUBE



XY180 S121 PUNK B

422 162 811 932 B

Options

XY180 CONNECTION BOX
COVERSET R 90-100

Accessories

HONEYCOMB 50
LINEAR SPREAD LENS 50
SPREAD LENS 50
SOFTENING LENS 50
GLASS SBL 50


For detailed installation instructions, please consult the manual: [422_162_811_XXX_HAND.pdf](#)

XY180 S121 PUNK B






422 162 811 932 B

FINISH YOUR SPECIFICATION

Coversets

	204 00 100 B COVERSET R 100 B	☐
	204 00 100 W COVERSET R 100 W	☐

Light altering devices

	413 03 01 B HONEYCOMB 50 B	☐
	413 03 02 LINEAR SPREAD LENS 50	☐
	413 03 03 SPREAD LENS 50	☐
	413 03 04 SOFTENING LENS 50	☐
	413 03 05 GLASS SBL 50	☐


XY180 S121 PUNK B

422 162 811 932 B

Finish your product

 53 414 01 00 B SPY TUBE B	☐
414 01 00 FBR SPY TUBE FBR	☐
414 01 00 FG SPY TUBE FG	☐
414 01 00 W SPY TUBE W	☐

Other

 33 Ø76 422 99 01 B XY180 CONNECTION BOX B	☐
---	--------------------------

Notes: