





M52 - 1 LED 82720 DIM5

24414 8225



 [View on website](#)

General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	non adjustable
INFORMATION	LENS FL-20° EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	F
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>80 / 2700K / 558lm
SDCM	SDCM2
LED TECHNICS (LIGHT SOURCE)	558lm // 6W // 94lm/W
LED TECHNICS (LUMINAIRE)	474lm // 7W // 69lm/W

Requirements

LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual: [24414_8X25_HAND.pdf](#)


M52 - 1 LED 82720 DIM5

24414 8225

FINISH YOUR SPECIFICATION


LED power supplies

#




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

14




300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

34



21012 0230 LED POWER SUPPLY 48V-DC / 100W

14



21012 0240 LED POWER SUPPLY 48V-DC / 200W

29


M52 - 1 LED 82720 DIM5

24414 8225


COMPATIBLE COMPOSABLES

SPLITLINE M52 profile


Available Colours




420 52 10 00 SPM52 - PROFILE 1m



420 52 20 00 SPM52 - PROFILE 2m



420 52 30 00 SPM52 - PROFILE 3m



24413 0000 SPM52 - PROFILE



Notes: