





M20/M26H - TWEETER BL 927 DIM5 B

23352 9205 B

AVAILABLE IN
BLACK 23352 9205 B
WHITE 23352 9205 W



 [View on website](#)

General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° to 45° swiveling, 355° rotatable
INFORMATION	EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	1020lm // 10W // 103lm/W

Remarks

Take a look at our **MAGNETIC PROFILES** movie

Requirements

BOWL GLASS CLEAR
 BOWL GLASS AMBER
 BOWL GLASS OPAL WHITE
 LED POWER SUPPLY 48V-DC

 DELTALIGHT®

M20/M26H - TWEETER BL 927 DIM5 B

23352 9205 B

For detailed installation instructions, please consult the manual: [23352_9X05_HAND.pdf](#)


M20/M26H - TWEETER BL 927 DIM5 B

23352 9205 B

FINISH YOUR SPECIFICATION


LED power supplies

#




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

8




300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

18



21012 0230 LED POWER SUPPLY 48V-DC / 100W


8




21012 0240 LED POWER SUPPLY 48V-DC / 200W

16


To be used with ...



286 67 01 BOWL GLASS CLEAR



286 67 02 BOWL GLASS AMBER



286 67 03 BOWL GLASS OPAL WHITE

M20/M26H - TWEETER BL 927 DIM5 B

23352 9205 B

COMPATIBLE COMPOSABLES

SHIFTLINE M26H + SBL


Available Colours




30411 9205 SHIFTLINE M26H + SBL 2m DIM5




30411 9305 SHIFTLINE M26H + SBL 2m DIM5




30412 9205 SHIFTLINE M26H + SBL 3m DIM5



30412 9305 SHIFTLINE M26H + SBL 3m DIM5



30413 9205 SHIFTLINE M26H + SBL 4m DIM5



30413 9305 SHIFTLINE M26H + SBL 4m DIM5




M20/M26H - TWEETER BL 927 DIM5 B


23352 9205 B

SHIFTLINE M26H profile


Available Colours




23359 0000 SLM26H - PROFILE



23359 0010 SLM26H - PROFILE 1m



23359 0020 SLM26H - PROFILE 2m



23359 0030 SLM26H - PROFILE 3m



SPLITLINE M20 ST profile

Available Colours



23397 0000 SPM20 ST - PROFILE



23397 0020 SPM20 ST - PROFILE 2m



23397 0030 SPM20 ST - PROFILE 3m




M20/M26H - TWEETER BL 927 DIM5 B


23352 9205 B

SPLITLINE M20 profile


Available Colours




420 20 10 00 SPM20 - PROFILE 1m



420 20 20 00 SPM20 - PROFILE 2m



420 20 30 00 SPM20 - PROFILE 3m



23301 0000 SPM20 - PROFILE B



Notes: