





FRAGMA S 93014 ADM B
23612 9310 B

AVAILABLE IN
BLACK 23612 9310 B
WHITE 23612 9310 W



 [View on website](#)

General info

	LOCATION	indoor
	INSTALLATION	Mains voltage track Mains voltage track mounted
	INGRESS PROTECTION	IP20
	WEIGHT (KG)	0.9
	ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
	INFORMATION	4 x LENS SP-14° INCL.LED POWER SUPPLY 900mA-DC 3F MULTI ADAPTER

Electrical info

	ELECTRICAL	110-240V / 50-60Hz
	CLASS	I
	POWER SUPPLY	YES
	DIM TYPE	non-dimmable
	ENERGY CLASS	E
	CERTIFICATES	CB, EAC, RCM

Lightsource info

	LIGHTSOURCE NAME	LED
	LIGHTSOURCE	LED cluster 10,4W / CRI>90 (R9: 64) / 3000K / 1180lm
	TM-30 VALUES	Rf: 92 / Rg: 99
	SDCM	SDCM3
	RISKGROUP	RG2
	LM80	L80 > 150000
	LED TECHNICS (LIGHT SOURCE)	1180lm // 10,4W // 113lm/W
	LED TECHNICS (LUMINAIRE)	988lm // 12W // 83lm/W

Requirements

TRACK 3F DIM

Options

FRAGMA 2X2 BEAM LENS

Accessories

FRAGMA 2X2 ACCESSORIES
Delta Light NV may revise the information and technical data at any time without notice. Version: 11/12/2024


FRAGMA S 93014 ADM B

23612 9310 B


For detailed installation instructions, please consult the manual: [23612_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Light altering devices




23613 0030 FRAGMA S BEAM LENS 26°

☐



23613 0060 FRAGMA S BEAM LENS 47°

☐



23613 0090 FRAGMA S SOFTENING LENS

☐



23613 0140 FRAGMA S LINEAR SPREAD LENS

☐


23613 0180 FRAGMA S WALLWASH LENS

☐


23613 0240 B FRAGMA S HONEYCOMB B

☐


23613 0270 B FRAGMA S RASTER B

☐

COMPATIBLE TRACKS

TRACK 3F DIM H			Available Colours
200 14 410	TRACK 3F DIM H 1m	1000 m 1.6 kg	 
200 14 420	TRACK 3F DIM H 2m	2000 m 3.2 kg	 
200 14 430	TRACK 3F DIM H 3m	3000 m 4.8 kg	 
TRACK 3F DIM IN			Available Colours
200 13 410	TRACK 3F DIM IN 1m	1000 m 1.2 kg	 
200 13 420	TRACK 3F DIM IN 2m	2000 m 2.4 kg	 
200 13 430	TRACK 3F DIM IN 3m	3000 m 3.5 kg	 
TRACK 3F DIM ON			Available Colours
200 12 410	TRACK 3F DIM ON 1m	1000 m 1.1 kg	 
200 12 420	TRACK 3F DIM ON 2m	2000 m 2.1 kg	 
200 12 430	TRACK 3F DIM ON 3m	3000 m 3.1 kg	 

Notes: