





FRAGMA L 93014 ADM B
23610 9310 B

AVAILABLE IN
BLACK 23610 9310 B
WHITE 23610 9310 W



 [View on website](#)



General info

LOCATION	indoor
INSTALLATION	Mains voltage track Mains voltage track mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.9
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	16 x LENS SP-14° INCL.LED POWER SUPPLY 900mA-DC 3F MULTI ADAPTER

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E
CERTIFICATES	CB, EAC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 41,6W / CRI>90 (R9: 64) / 3000K / 4718lm
TM-30 VALUES	Rf: 92 / Rg: 99
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
LED TECHNICS (LIGHT SOURCE)	4718lm // 41,6W // 113lm/W
LED TECHNICS (LUMINAIRE)	3811lm // 48W // 80lm/W

Requirements

TRACK 3F DIM

Options

FRAGMA 4X4 BEAM LENS

Accessories

FRAGMA 4X4 ACCESSORIES
Delta Light NV may revise the information and technical data at any time without notice. Version: 11/12/2024



FRAGMA L 93014 ADM B

23610 9310 B









For detailed installation instructions, please consult the manual: [23610_XXX0_HAND.pdf](#)

FRAGMA L 93014 ADM B

23610 9310 B

FINISH YOUR SPECIFICATION

Light altering devices

	23613 0010 FRAGMA L BEAM LENS 26°	☐
	23613 0040 FRAGMA L BEAM LENS 47°	☐
	23613 0070 FRAGMA L SOFTENING LENS	☐
	23613 0100 FRAGMA L LINEAR SPREAD LENS	☐
	23613 0160 FRAGMA L WALLWASH LENS	☐
	23613 0190 B FRAGMA L FLAPS B	☐
	23613 0220 B FRAGMA L HONEYCOMB B	☐
	23613 0250 B FRAGMA L RASTER B	☐

COMPATIBLE TRACKS

TRACK 3F DIM H			Available Colours
200 14 410	TRACK 3F DIM H 1m	1000 m 1.6 kg	 
200 14 420	TRACK 3F DIM H 2m	2000 m 3.2 kg	 
200 14 430	TRACK 3F DIM H 3m	3000 m 4.8 kg	 
TRACK 3F DIM IN			Available Colours
200 13 410	TRACK 3F DIM IN 1m	1000 m 1.2 kg	 
200 13 420	TRACK 3F DIM IN 2m	2000 m 2.4 kg	 
200 13 430	TRACK 3F DIM IN 3m	3000 m 3.5 kg	 
TRACK 3F DIM ON			Available Colours
200 12 410	TRACK 3F DIM ON 1m	1000 m 1.1 kg	 
200 12 420	TRACK 3F DIM ON 2m	2000 m 2.1 kg	 
200 12 430	TRACK 3F DIM ON 3m	3000 m 3.1 kg	 

Notes: