



BOXY XL S 93020 DIM5 B-B



10723 9315 B-B

AVAILABLE IN

BLACK-BLACK 10723 9315 B-B

WHITE-BLACK 10723 9315 W-B

WHITE-WHITE 10723 9315 W-W



 [View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.3
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-20° INCL.DIMMABLE LED POWER SUPPLY 500mA-DC

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	C
CERTIFICATES	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 16,3W / CRI>90 (R9: 52) / 3000K / 2309lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUPE	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	2309lm // 16,3W // 142lm/W
LED TECHNICS (LUMINAIRE)	2016lm // 19W // 108lm/W

Accessories

HONEYCOMB 78
SOFTENING LENS 78
GLASS SBL 78


BOXY XL S 93020 DIM5 B-B

10723 9315 B-B

For detailed installation instructions, please consult the manual: [10723_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Light altering devices



Ø78

201 02 01 B HONEYCOMB 78 B



Ø78

201 02 04 SOFTENING LENS 78



Ø78

201 02 05 GLASS SBL 78

Notes: