





INFORM R1 DOWN 92748 B-B

26811 9220 B-B

AVAILABLE IN
BLACK-BLACK 26811 9220 B-B
BLACK-FLEMISH GOLD 26811 9220 B-FG
FLEMISH GOLD-BLACK 26811 9220 FG-B
WHITE-BLACK 26811 9220 W-B
WHITE-WHITE 26811 9220 W-W



[View on website](#)

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted,Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.8
ADJUSTABILITY	non adjustable
INFORMATION	96 x REFLECTOR WFL-71° EXCL.LED POWER SUPPLY 700mA-DC

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	C
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 22,9W / CRI>90 (R9: 50) / 2700K / 3456lm
SDCM	SDCM3
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	3456lm // 22,9W // 151lm/W
LED TECHNICS (LUMINAIRE)	2886lm // 26W // 110lm/W

Requirements	
LED POWER SUPPLY 700mA-DC DIM (Remote)	

Options	
SUSPENSION SET 30 2x0,75 1,6m	
CABLE BASE R / S	
COVERSET R 62-90-100 / S 62-80-90	



INFORM R1 DOWN 92748 B-B

26811 9220 B-B



For detailed installation instructions, please consult the manual: [**26811_XXX0_HAND.pdf**](#)

INFORM R1 DOWN 92748 B-B

26811 9220 B-B


FINISH YOUR SPECIFICATION

Current supply


	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

LED power supplies

#

	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5	1 ☐
--	--	----------------------------

Coversets

	204 00 100 B COVERSET R 100 B	☐
	204 00 100 W COVERSET R 100 W	☐

INFORM R1 DOWN 92748 B-B

26811 9220 B-B

Suspension parts



15225 0300 B SUSPENSION SET 30 2x0,75 1,6m B

☐

15225 0300 W SUSPENSION SET 30 2x0,75 1,6m W

☐

Electric connection parts



15225 0360 B CONNECTION ST B

☐

15225 0360 W CONNECTION ST W

☐

Notes: