


26215 9208 B

Technical drawing of an extruded aluminum profile. The profile has a total length of 230mm, a height of 40mm, and a base thickness of 30mm. It features two circular holes with a diameter of Ø60mm, spaced 100mm apart. The distance from the left edge to the first hole is 24mm, and from the second hole to the right edge is 7mm. The holes are positioned 15mm from the top and 19mm from the bottom of the profile. A dimension of Ø38 is also indicated near the holes.



[View on website](#)

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.7
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	INCL.4 x INTERCHANGABLE REFLECTOR: FL-28° + WFL-41° INCL.DIMMABLE LED POWER SUPPLY 350mA-DC

ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, RCM

	LIGHTSOURCE NAME	LED
	LIGHTSOURCE	2 x (LED array 5,8W / CRI>90 (R9: 60) / 2700K / 702lm)
	TM-30 VALUES	rf: 89 / Rg: 100
	SDCM	SDCM1
	RISKGROUP	RG1
	LM80	L90B10 > 50000
	LED TECHNICS (LIGHT SOURCE)	1404lm // 11,6W // 121lm/W
	LED TECHNICS (LUMINAIRE)	1177lm // 13W // 88lm/W

ODRON COVER

Delta Light NV may revise the information and technical data at any time without notice. Version: 29/11/2024

ODRON ON 2 92728/41 DIM8 B

26215 9208 B

FINISH YOUR SPECIFICATION

Decorative ornaments



26210 0020 GC ODRON COVER GC

☐

Notes: