



CONFORM P28 PDS DOWN-UP 953067 B-B



26516 7320 B-B

AVAILABLE IN

BLACK-BLACK 26516 7320 B-B

BLACK-FLEMISH GOLD 26516 7320 B-FG

WHITE-BLACK 26516 7320 W-B



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	8
ADJUSTABILITY	non adjustable
INFORMATION	120 x REFLECTOR FL-67° (DOWN) INCL.DIMMABLE LED POWER SUPPLY 1300mA-DC DOWN / 1000mA-DC UP INCL.PRESENCE & DAYLIGHT SENSOR INCL.2 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 3 x 0.75mm ² NATURAL LIGHT TECHNOLOGY

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 43,9W / CRI>95 (R9: 80) / 3000K / 5136lm UP: LED cluster 33,7W / CRI>95 (R9: 80) / 3000K / 3955lm
TM-30 VALUES	Rf: 94 / Rg: 103
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN: 5136lm // 43,9W // 117lm/W UP: 3955lm // 33,7W // 117lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 3225lm // 50W // 64lm/W UP: 3117lm // 39W // 80lm/W

CONFORM P28 PDS DOWN-UP 953067 B-B

26516 7320 B-B

Options

CABLE BASE R / S

COVERSET R 62-90-100 / S 62-80-90

CONNECTION ST / CONNECTION TRIMLESS

SUSPENSION ST / SUSPENSION TRIMLESS



For detailed installation instructions, please consult the manual: [26516_XXX0_HAND.pdf](#)

CONFORM P28 PDS DOWN-UP 953067 B-B


26516 7320 B-B

FINISH YOUR SPECIFICATION

Current supply

	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐


Coversets

	204 00 100 B COVERSET R 100 B	☐
	204 00 100 W COVERSET R 100 W	☐


CONFORM P28 PDS DOWN-UP 953067 B-B

26516 7320 B-B

Suspension parts



328 10 01 SUSPENSION TRIMLESS O.F.A.

☐


15225 0340 B SUSPENSION ST B

☐

15225 0340 W SUSPENSION ST W

☐

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.

☐


15225 0360 B CONNECTION ST B

☐


15225 0360 W CONNECTION ST W

☐

Other



26510 0010 PDS REMOTE CONTROL

☐

26510 0020 PDS SENSOR PROGRAMMER

☐



CONFORM P28 PDS DOWN-UP 953067 B-B

26516 7320 B-B

Notes: