



CONFORM P28 PDS DOWN-UP 954067 W-B



26516 7420 W-B

AVAILABLE IN

BLACK-BLACK 26516 7420 B-B

BLACK-FLEMISH GOLD 26516 7420 B-FG

WHITE-BLACK 26516 7420 W-B



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	8
ADJUSTABILITY	non adjustable
INFORMATION	120 x REFLECTOR FL-67° (DOWN) INCL.DIMMABLE LED POWER SUPPLY 1300mA-DC DOWN / 1000mA-DC UP INCL.PRESENCE & DAYLIGHT SENSOR INCL.2 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 3 x 0.75mm ² NATURAL LIGHT TECHNOLOGY

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 43,9W / CRI>95 (R9: 50) / 4000K / 5388lm UP: LED cluster 33,7W / CRI>95 (R9: 50) / 4000K / 4157lm
SDCM	SDCM3
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN: 5388lm // 43,9W // 123lm/W UP: 4157lm // 33,7W // 123lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 3384lm // 50W // 67lm/W UP: 3276lm // 39W // 85lm/W

Options

CABLE BASE R / S

COVERSET R 62-90-100 / S 62-80-90

CONNECTION ST / CONNECTION TRIMLESS

SUSPENSION ST / SUSPENSION TRIMLESS

Delta Light NV may revise the information and technical data at any time without notice. Version: 02/03/2025



CONFORM P28 PDS DOWN-UP 954067 W-B

26516 7420 W-B


For detailed installation instructions, please consult the manual: [**26516_XXX0_HAND.pdf**](#)

CONFORM P28 PDS DOWN-UP 954067 W-B

26516 7420 W-B

FINISH YOUR SPECIFICATION

Current supply



	☐ 203 99 55 ANO CABLE BASE R ANO
	☐ 203 99 55 B CABLE BASE R B
	☐ 203 99 55 W CABLE BASE R W
	☐ 203 99 56 ANO CABLE BASE S ANO
	☐ 203 99 56 B CABLE BASE S B
	☐ 203 99 56 W CABLE BASE S W

Coversets


	☐ <u>204 00 100 B</u> COVERSET R 100 B
	☐ <u>204 00 100 W</u> COVERSET R 100 W

CONFORM P28 PDS DOWN-UP 954067 W-B
26516 7420 W-B



Suspension parts

	328 10 01	SUSPENSION TRIMLESS O.F.A.	☐
	15225 0340 B	SUSPENSION ST B	☐
	15225 0340 W	SUSPENSION ST W	☐

Electric connection parts

	328 10 03	CONNECTION TRIMLESS O.F.A.	☐
	15225 0360 B	CONNECTION ST B	☐
	15225 0360 W	CONNECTION ST W	☐

Other

	26510 0010	PDS REMOTE CONTROL	☐
	26510 0020	PDS SENSOR PROGRAMMER	☐



CONFORM P28 PDS DOWN-UP 954067 W-B

26516 7420 W-B

Notes: