





LOGIC 90 S 24V 93011 ANO
13967 9310 ANO

AVAILABLE IN
ALU ANODIZED 13967 9310 ANO



 [View on website](#)



General info	
LOCATION	outdoor
INSTALLATION	Floor Recessed
CUTOUT SHAPE/SIZE (MM)	square - 112 x 112
RECESSED DEPTH (MM)	125
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK07
WEIGHT (KG)	1.1
ADJUSTABILITY	non adjustable
INFORMATION	INCL.CABLE H05 RN-F 2 x 1mm ² 0,5m REFLECTOR SP-11° EXCL.LED POWER SUPPLY 24V-DC (non-dimmable or dimmable with PWM output) IEC 60598-2-13 : max.150kg 25N/cm ² ESG 5mm
Electrical info	
ELECTRICAL	24V-DC
CLASS	III
DIM TYPE	non-dimmable
ENERGY CLASS	D
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	787lm // 5,8W // 135lm/W
LED TECHNICS (LUMINAIRE)	741lm // 7W // 111lm/W

Requirements
LED POWER SUPPLY 24V-DC

Options
LOGIC 90 BOX S
CBOX
Delta Light NV may revise the information and technical data at any time without notice. Version: 18/12/2024



LOGIC 90 S 24V 93011 ANO

13967 9310 ANO

For detailed installation instructions, please consult the manual: [**13967_XXX0_HAND.pdf**](#)


LOGIC 90 S 24V 93011 ANO

13967 9310 ANO

FINISH YOUR SPECIFICATION


LED power supplies

#



300 89 24 150 LED POWER SUPPLY 24V-DC / 150W

21


☐


21012 0160 LED POWER SUPPLY 24V-DC / 24W

3

☐


Miscellaneous control equipment



21032 0320 AMBIENT LIGHT SENSOR AND 24V DIMMER (PWM)

☐


Ground mounting boxes



213 19 08 LOGIC 90 BOX S

☐

Waterproof connection parts



216 12 00 CBOX

☐



LOGIC 90 S 24V 93011 ANO

13967 9310 ANO

Notes: