





LOGIC 90 R A WALLWASH 24V 930 SBL ANO

13971 9300 ANO

AVAILABLE IN
ALU ANODIZED 13971 9300 ANO
BLACK 13971 9300 B



[View on website](#)



General info

LOCATION	outdoor
INSTALLATION	Floor Recessed
CUTOUT SHAPE/SIZE (MM)	round - 93
RECESSED DEPTH (MM)	125
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK07
WEIGHT (KG)	1
ADJUSTABILITY	non adjustable
INFORMATION	INCL.CABLE H05 RN-F 2 x 1mm ² 0,5m EXCLLED POWER SUPPLY 24V-DC (non-dimmable or dimmable with PWM output) IEC 60598-2-13 : max.150kg 25N/cm ² ESG 5mm

Electrical info

ELECTRICAL	24V-DC
CLASS	III
DIM TYPE	non-dimmable
ENERGY CLASS	E

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	787lm // 5,8W // 135lm/W
LED TECHNICS (LUMINAIRE)	401lm // 7W // 60lm/W

Requirements

LED POWER SUPPLY 24V-DC

LOGIC 90 R A WALLWASH 24V 930 SBL ANO

13971 9300 ANO

Options

LOGIC 90 BOX R

CBOX

For detailed installation instructions, please consult the manual: [13971_XXX0_HAND.pdf](#)


LOGIC 90 R A WALLWASH 24V 930 SBL ANO

13971 9300 ANO

FINISH YOUR SPECIFICATION


LED power supplies

#



300 89 24 150 LED POWER SUPPLY 24V-DC / 150W


21



21012 0160 LED POWER SUPPLY 24V-DC / 24W


3

Miscellaneous control equipment




21032 0320 AMBIENT LIGHT SENSOR AND 24V DIMMER (PWM)

Ground mounting boxes



213 19 09 LOGIC 90 BOX R

Waterproof connection parts



216 12 00 CBOX



LOGIC 90 R A WALLWASH 24V 930 SBL ANO

13971 9300 ANO

Notes: