



MULTINOVA 255 930 DIM4 B



28056 9304 B

AVAILABLE IN

BLACK 28056 9304 B

GOLD COLOURED 28056 9304 GC

WHITE 28056 9304 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	9.2
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL INCL.DIMMABLE LED POWER SUPPLY INCL.2 x CABLE SUSPENSION SINGLE AUTO. 3.0m INCL.1 x CABLE 5 x 0.75mm ²

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI or DSI or push button
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED cluster 34,4W / CRI>90 (R9: 68) / 3000K / 4767lm)
TM-30 VALUES	Rf: 89 / Rg: 97
SDCM	SDCM3
LM80	L70 > 60000
LED TECHNICS (LIGHT SOURCE)	9534lm // 68,8W // 139lm/W
LED TECHNICS (LUMINAIRE)	7683lm // 79W // 97lm/W

Options

CABLE BASE R / S

COVERSET R 62-90-100

CONNECTION ST / CONNECTION TRIMLESS

SUSPENSION ST / SUSPENSION TRIMLESS



MULTINOVA 255 930 DIM4 B

28056 9304 B



For detailed installation instructions, please consult the manual: [28056_XXX4_HAND.pdf](#)

MULTINOVA 255 930 DIM4 B


28056 9304 B

FINISH YOUR SPECIFICATION

Current supply

	<u>203 99 55 ANO</u> CABLE BASE R ANO	☐
	<u>203 99 55 B</u> CABLE BASE R B	☐
	<u>203 99 55 W</u> CABLE BASE R W	☐
	<u>203 99 56 ANO</u> CABLE BASE S ANO	☐
	<u>203 99 56 B</u> CABLE BASE S B	☐
	<u>203 99 56 W</u> CABLE BASE S W	☐


Coversets

	<u>204 00 100 B</u> COVERSET R 100 B	☐
	<u>204 00 100 W</u> COVERSET R 100 W	☐

MULTINOVA 255 930 DIM4 B


28056 9304 B

Suspension parts



328 10 01

SUSPENSION TRIMLESS O.F.A.

☐

15225 0340 B

SUSPENSION ST B


☐

15225 0340 W

SUSPENSION ST W

☐

Electric connection parts



328 10 03

CONNECTION TRIMLESS O.F.A.

☐

15225 0360 B

CONNECTION ST B

☐

15225 0360 W

CONNECTION ST W

☐

Notes: