





MULTINOVA 255 PRISM 930 DIM4 B

28057 9304 B

AVAILABLE IN
BLACK 28057 9304 B
WHITE 28057 9304 W



 [View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	9.2
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC PRISMATIC INCL.DIMMABLE LED POWER SUPPLY INCL.2 x CABLE SUSPENSION SINGLE AUTO. 3.0m INCL.1 x CABLE 5 x 0.75mm ²

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI or DSI or push button
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED cluster 34,4W / CRI>90 (R9: 68) / 3000K / 4767lm)
TM-30 VALUES	Rf: 89 / Rg: 97
SDCM	SDCM3
LM80	L70 > 60000
LED TECHNICS (LIGHT SOURCE)	9534lm // 68,8W // 139lm/W
LED TECHNICS (LUMINAIRE)	6932lm // 79W // 88lm/W

Options

CABLE BASE R / S
COVERSET R 62-90-100
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS



MULTINOVA 255 PRISM 930 DIM4 B

28057 9304 B


For detailed installation instructions, please consult the manual: [28057_XXX4_HAND.pdf](#)

MULTINOVA 255 PRISM 930 DIM4 B

28057 9304 B

FINISH YOUR SPECIFICATION

Current supply



41

203 99 55 ANO CABLE BASE R ANO

☐

203 99 55 B CABLE BASE R B

☐

203 99 55 W CABLE BASE R W

☐



41

203 99 56 ANO CABLE BASE S ANO

☐


203 99 56 B CABLE BASE S B

☐

203 99 56 W CABLE BASE S W

☐

Coversets



204 00 100 B COVERSET R 100 B

☐


204 00 100 W COVERSET R 100 W

☐

MULTINOVA 255 PRISM 930 DIM4 B

28057 9304 B

Suspension parts



328 10 01 SUSPENSION TRIMLESS O.F.A.

☐




15225 0340 B SUSPENSION ST B

☐

15225 0340 W SUSPENSION ST W

☐

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.

☐



15225 0360 B CONNECTION ST B

☐

15225 0360 W CONNECTION ST W

☐

Notes: