





MULTINOVA 255 SOFT 930 DIM5 B
28061 9005 B

AVAILABLE IN
BLACK 28061 9005 B
GOLD COLOURED 28061 9005 GC
WHITE 28061 9005 W



 [View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	9.2
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL INCL.DIMMABLE LED POWER SUPPLY INCL.2 x CABLE SUSPENSION SINGLE AUTO. 3.0m INCL.1 x CABLE 5 x 0.75mm ²

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED cluster 32,3W / CRI>90 (R9: 50) / 3000K-1800K / 4567lm)
TM-30 VALUES	Rf: 89,4 / Rg: 98,6
SDCM	SDCM3
RISKGROUP	RG1
LM80	L70 > 60000
LED TECHNICS (LIGHT SOURCE)	9134lm // 64,6W // 141lm/W
LED TECHNICS (LUMINAIRE)	7361lm // 74W // 99lm/W

Options

CABLE BASE R / S
COVERSET R 62-90-100
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS



MULTINOVA 255 SOFT 930 DIM5 B

28061 9005 B


For detailed installation instructions, please consult the manual: [**28061_XXX5_HAND.pdf**](#)

MULTINOVA 255 SOFT 930 DIM5 B

28061 9005 B

FINISH YOUR SPECIFICATION

Current supply



41 **203 99 55 ANO** CABLE BASE R ANO

☐

203 99 55 B CABLE BASE R B

☐

203 99 55 W CABLE BASE R W

☐

41 **203 99 56 ANO** CABLE BASE S ANO

☐


203 99 56 B CABLE BASE S B

☐

203 99 56 W CABLE BASE S W

☐

Coversets



204 00 100 B COVERSET R 100 B



☐

204 00 100 W COVERSET R 100 W


☐

MULTINOVA 255 SOFT 930 DIM5 B
28061 9005 B

Suspension parts

	328 10 01	SUSPENSION TRIMLESS O.F.A.	☐
	15225 0340 B	SUSPENSION ST B	☐
	15225 0340 W	SUSPENSION ST W	☐

Electric connection parts

	328 10 03	CONNECTION TRIMLESS O.F.A.	☐
	15225 0360 B	CONNECTION ST B	☐
	15225 0360 W	CONNECTION ST W	☐

Notes: