





MULTINOVA 255 TW PRISM 930 DIM5 B

28060 9005 B

AVAILABLE IN

BLACK 28060 9005 B

WHITE 28060 9005 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	9.2
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC PRISMATIC INCL.DIMMABLE LED POWER SUPPLY - DALI (DT8) INCL.2 x CABLE SUSPENSION SINGLE AUTO. 3.0m INCL.1 x CABLE 5 x 0.75mm ²

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	@ 2700K: 2 x (LED cluster 31W / CRI>90 (R9: 63) / 2700K-6500K / 4430lm) Or @ 6500K: 2 x (LED cluster 31,1W / CRI>90 (R9: 81) / 2700K-6500K / 4746lm)
SDCM	SDCM3
RISKGROUP	RG0
LM80	L70 > 60000
LED TECHNICS (LIGHT SOURCE)	@ 2700K: 8860lm // 62W // 143lm/W Or @ 6500K: 9492lm // 62,2W // 153lm/W
LED TECHNICS (LUMINAIRE)	@ 2700K: 6442lm // 71W // 90lm/W Or @ 6500K: 6902lm // 72W // 96lm/W

MULTINOVA 255 TW PRISM 930 DIM5 B

28060 9005 B

Options

CABLE BASE R / S

COVERSET R 62-90-100

CONNECTION ST / CONNECTION TRIMLESS



SUSPENSION ST / SUSPENSION TRIMLESS

For detailed installation instructions, please consult the manual: [28060_XXX5_HAND.pdf](#)


MULTINOVA 255 TW PRISM 930 DIM5 B
28060 9005 B

FINISH YOUR SPECIFICATION

Current supply


	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

Coversets

	204 00 100 B COVERSET R 100 B	☐
	204 00 100 W COVERSET R 100 W	☐

MULTINOVA 255 TW PRISM 930 DIM5 B
28060 9005 B

Suspension parts



328 10 01 SUSPENSION TRIMLESS O.F.A.

☐




15225 0340 B SUSPENSION ST B

☐

15225 0340 W SUSPENSION ST W

☐

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.

☐



15225 0360 B CONNECTION ST B

☐

15225 0360 W CONNECTION ST W

☐

Notes: