


27934 9005 B

Technical drawing of a circular component. The drawing shows a top view of a circular part with a diameter of 300 mm (Ø300). A cross-section is indicated by a line with a break, showing a thickness of 45 mm. Other dimensions shown are 259 mm (overall width), 32 mm (inner diameter of the cross-section), 43 mm (height of the cross-section), and 47 mm (height of the main body).



General info

LOCATION	indoor
INSTALLATION	Mains voltage track Mains voltage track mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.5
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC PRISMATIC 3F MULTI DIMMABLE POWER ADAPTER - (DALI DT8)

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	CB, RCM

Lightsource info

LIGHTSOURCE INFO	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	@ 2700K: LED cluster 9,4W / CRI>90 (R9: 63) / 2700K-6500K / 1338lm Or @ 6500K: LED cluster 9,4W / CRI>90 (R9: 81) / 2700K-6500K / 1428lm
SDCM	SDCM3
RISKGROUP	RG0
LM80	L70 > 60000
LED TECHNICS (LIGHT SOURCE)	@ 2700K: 1338lm // 9,4W // 142lm/W Or @ 6500K: 1428lm // 9,4W // 152lm/W
LED TECHNICS (LUMINAIRE)	@ 2700K: 883lm // 11W // 82lm/W Or @ 6500K: 942lm // 11W // 87lm/W

Requirements

TRACK 3F DIM

MULTINOVA 30 TW PRISM 930 ADM DIM5 B
 27934 9005 B

For detailed installation instructions, please consult the manual: [27934_XXX5_HAND.pdf](#)

COMPATIBLE TRACKS

TRACK 3F DIM H			Available Colours
200 14 410	TRACK 3F DIM H 1m	1000 m 1.6 kg	 
200 14 420	TRACK 3F DIM H 2m	2000 m 3.2 kg	 
200 14 430	TRACK 3F DIM H 3m	3000 m 4.8 kg	 
TRACK 3F DIM IN			Available Colours
200 13 410	TRACK 3F DIM IN 1m	1000 m 1.2 kg	 
200 13 420	TRACK 3F DIM IN 2m	2000 m 2.4 kg	 
200 13 430	TRACK 3F DIM IN 3m	3000 m 3.5 kg	 
TRACK 3F DIM ON			Available Colours
200 12 410	TRACK 3F DIM ON 1m	1000 m 1.1 kg	 
200 12 420	TRACK 3F DIM ON 2m	2000 m 2.1 kg	 
200 12 430	TRACK 3F DIM ON 3m	3000 m 3.1 kg	 

Notes: