





MULTINOVA 355 SOFT 930 DIM5 B

28067 9005 B

AVAILABLE IN
BLACK 28067 9005 B
GOLD COLOURED 28067 9005 GC
WHITE 28067 9005 W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	14
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL INCL.DIMMABLE LED POWER SUPPLY INCL.3 x CABLE SUSPENSION SINGLE AUTO. 3.0m INCL.1 x CABLE 5 x 0.75mm ²

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	3 x (LED cluster 32,3W / CRI>90 (R9: 50) / 3000K-1800K / 4567lm)
TM-30 VALUES	Rf: 89,4 / Rg: 98,6
SDCM	SDCM3
RISKGROUP	RG1
LM80	L70 > 60000
LED TECHNICS (LIGHT SOURCE)	13701lm // 96,9W // 141lm/W
LED TECHNICS (LUMINAIRE)	11042lm // 111W // 99lm/W

Options

CABLE BASE R / S
COVERSET R 62-90-100
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS



MULTINOVA 355 SOFT 930 DIM5 B

28067 9005 B


For detailed installation instructions, please consult the manual: [28067_XXX5_HAND.pdf](#)

MULTINOVA 355 SOFT 930 DIM5 B

28067 9005 B

FINISH YOUR SPECIFICATION

Current supply




41 **203 99 55 ANO** CABLE BASE R ANO

☐

203 99 55 B CABLE BASE R B

☐

203 99 55 W CABLE BASE R W

☐

41 **203 99 56 ANO** CABLE BASE S ANO

☐


203 99 56 B CABLE BASE S B

☐

203 99 56 W CABLE BASE S W

☐

Coversets



204 00 100 B COVERSET R 100 B

☐


204 00 100 W COVERSET R 100 W

☐

MULTINOVA 355 SOFT 930 DIM5 B


28067 9005 B

Suspension parts



328 10 01

SUSPENSION TRIMLESS O.F.A.

☐

15225 0340 B

SUSPENSION ST B


☐

15225 0340 W

SUSPENSION ST W

☐

Electric connection parts



328 10 03

CONNECTION TRIMLESS O.F.A.

☐

15225 0360 B

CONNECTION ST B

☐

15225 0360 W

CONNECTION ST W

☐

Notes: