



MULTINOVA 55 OK 800 930 DIM4 B



28025 9304 B

AVAILABLE IN

BLACK 28025 9304 B

GOLD COLOURED 28025 9304 GC

WHITE 28025 9304 W



 [View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	8.5
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	INCL.PC SBL ADJUSTABLE 0-90°/355° INCL.DIMMABLE LED POWER SUPPLY

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY INCLUDED	YES
DIM TYPE	DALI or DSI or push button
ENERGY CLASS	D

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 34,4W / CRI>90 (R9: 68) / 3000K / 4767lm
TM-30 VALUES	Rf: 89 / Rg: 97
SDCM	SDCM3
LM80	L70 > 60000
LED TECHNICS (LIGHT SOURCE)	4767lm // 34,4W // 139lm/W
LED TECHNICS (LUMINAIRE)	3842lm // 40W // 97lm/W

Options

COVERSET R 62-90-100


For detailed installation instructions, please consult the manual: [28025_XXX4_HAND.pdf](#)

MULTINOVA 55 OK 800 930 DIM4 B

28025 9304 B

FINISH YOUR SPECIFICATION

Coversets



204 00 100 B COVERSET R 100 B

204 00 100 W COVERSET R 100 W

Notes: