





SPL14 - SPY 20 L 92730 MDL B

27319 9220 B

AVAILABLE IN
BLACK 27319 9220 B
FLEMISH BRONZE 27319 9220 FBR
FLEMISH GOLD 27319 9220 FG
GOLD COLOURED 27319 9220 GC
WHITE 27319 9220 W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.1
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-30° EXCLLED POWER SUPPLY 48V-DC SPY 20 TUBE B included

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 2W / CRI>90 (R9: 55) / 2700K / 220lm
TM-30 VALUES	rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L90B10 > 150000
LED TECHNICS (LIGHT SOURCE)	220lm // 2W // 110lm/W
LED TECHNICS (LUMINAIRE)	166lm // 2W // 72lm/W

Requirements

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

SPL14 - SPY 20 L 92730 MDL B


27319 9220 B

For detailed installation instructions, please consult the manual: [27319_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION


SMART 48

#



300 90 011 SMART 48 MODULATOR DIM9

72




300 90 012 SMART 48 MODULATOR WD

72


LED power supplies

#




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

37




300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

90



21012 0230 LED POWER SUPPLY 48V-DC / 100W

37



21012 0240 LED POWER SUPPLY 48V-DC / 200W

75


SPL14 - SPY 20 L 92730 MDL B

27319 9220 B


COMPATIBLE COMPOSABLES

D-LINER SHIFTLINE 19

Available Colours



29110 0010 D-LINER 19 SL PROFILE SET SAPP 2m




29110 0030 D-LINER 19 SL PROFILE SET 30BD 2m




SPLITLINE 14 profile

Available Colours



27300 0020 SPL14 - PROFILE 2m



27300 0030 SPL14 - PROFILE 3m



Notes: