





M20/M26H - HALOSCAN HP SOFT 93021 MDL W

23143 9020 W

AVAILABLE IN
BLACK 23143 9020 B
WHITE 23143 9020 W



 [View on website](#)

General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 45° swiveling, 355° rotatable
INFORMATION	LENS FL-21° EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	E
CERTIFICATES	ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 11,8W / CRI>90 (R9: 50) / 3000K-1800K / 1307lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1307lm // 11,8W // 110lm/W
LED TECHNICS (LUMINAIRE)	1071lm // 14W // 79lm/W

Remarks

Take a look at our **MAGNETIC PROFILES** movie

Requirements

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

Delta Light NV may revise the information and technical data at any time without notice. Version: 01/03/2025

M20/M26H - HALOSCAN HP SOFT 93021 MDL W

23143 9020 W

Accessories

HALOSCAN HONEYCOMB


HALOSCAN LINEAR SPREAD LENS

For detailed installation instructions, please consult the manual: [23143_XXX0_HAND.pdf](#)

M20/M26H - HALOSCAN HP SOFT 93021 MDL W
23143 9020 W

FINISH YOUR SPECIFICATION


Current supply #



21032 0030 SMART 48 MODULATOR PLUG-IN WD


14 ☐

SMART 48 #



300 90 011 SMART 48 MODULATOR DIM9


14 ☐



300 90 012 SMART 48 MODULATOR WD


14 ☐

LED power supplies #




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

7 ☐




300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

17 ☐



21012 0230 LED POWER SUPPLY 48V-DC / 100W

7 ☐




21012 0240 LED POWER SUPPLY 48V-DC / 200W

14 ☐

M20/M26H - HALOSCAN HP SOFT 93021 MDL W
23143 9020 W

Light altering devices



Ø72

² **23110 0040** HALOSCAN LINEAR SPREAD LENS

☐







Ø72

² **23110 0050 B** HALOSCAN HONEYCOMB B





☐

M20/M26H - HALOSCAN HP SOFT 93021 MDL W
23143 9020 W

COMPATIBLE COMPOSABLES

SHIFTLINE M26H profile		Available Colours
	23359 0000 SLM26H - PROFILE	 
	23359 0010 SLM26H - PROFILE 1m	 
	23359 0020 SLM26H - PROFILE 2m	       
	23359 0030 SLM26H - PROFILE 3m	       
SPLITLINE M20 ST profile		Available Colours
	23397 0000 SPM20 ST - PROFILE	 
	23397 0020 SPM20 ST - PROFILE 2m	 
	23397 0030 SPM20 ST - PROFILE 3m	 

M20/M26H - HALOSCAN HP SOFT 93021 MDL W
23143 9020 W

SPLITLINE M20 profile		Available Colours
	420 20 10 00 SPM20 - PROFILE 1m	
	420 20 20 00 SPM20 - PROFILE 2m	
	420 20 30 00 SPM20 - PROFILE 3m	
	23301 0000 SPM20 - PROFILE B	

Notes: