





**M26L - MULTINOVA 30 TW PRISM
930 DIM5 B**
27945 9005 B

AVAILABLE IN
BLACK 27945 9005 B
WHITE 27945 9005 W



 [View on website](#)

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.5
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC PRISMATIC EXCL.LED POWER SUPPLY 48V-DC DALI DT8 dimming

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 9,4W / CRI>90 (R9: 63) / 2700K-6500K / 1338lm
SDCM	SDCM3
RISKGROUP	RG0
LM80	L70 > 60000
LED TECHNICS (LIGHT SOURCE)	1338lm // 9,4W // 142lm/W
LED TECHNICS (LUMINAIRE)	883lm // 11W // 82lm/W

Remarks
Take a look at our **MAGNETIC PROFILES** movie

Requirements
LED POWER SUPPLY 48V-DC

M26L - MULTINOVA 30 TW PRISM 930 DIM5 B


27945 9005 B

For detailed installation instructions, please consult the manual: [27945_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION


LED power supplies

#




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

9




300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

22



21012 0230 LED POWER SUPPLY 48V-DC / 100W

9



21012 0240 LED POWER SUPPLY 48V-DC / 200W

18


M26L - MULTINOVA 30 TW PRISM 930 DIM5 B

27945 9005 B


COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)


Available Colours




23358 0000 SLM26L - PROFILE



23358 0010 SLM26L - PROFILE 1m



23358 0020 SLM26L - PROFILE 2m



23358 0030 SLM26L - PROFILE 3m



Notes: