





M20/M26H - SPY 52 TW 96520 DIM5 W

23331 9025 W

AVAILABLE IN
BLACK 23331 9025 B
WHITE 23331 9025 W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-20° EXCL. LED POWER SUPPLY 48V-DC DALI DT8 dimming Optional REFLECTORS 30° & 45° available

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	ENEC, LCA

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9W / CRI>90 (R9: 50) / 2700K-6500K / 1087lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1087lm // 9W // 121lm/W
LED TECHNICS (LUMINAIRE)	681lm // 10W // 66lm/W

Remarks

Take a look at our [MAGNETIC PROFILES movie](#)

Requirements

SPY 52 TUBE
LED POWER SUPPLY 48V-DC

M20/M26H - SPY 52 TW 96520 DIM5 W

23331 9025 W

Accessories

HONEYCOMB 42

SPREAD LENS 42

LINEAR SPREAD LENS 42





SOFTENING LENS 42

GLASS SBL 42

For detailed installation instructions, please consult the manual: [23331_XXX5_HAND.pdf](#)

M20/M26H - SPY 52 TW 96520 DIM5 W
23331 9025 W

FINISH YOUR SPECIFICATION






LED power supplies		#
	300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN	9 ☐
	300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN	23 ☐
	21012 0230 LED POWER SUPPLY 48V-DC / 100W	9 ☐
	21012 0240 LED POWER SUPPLY 48V-DC / 200W	19 ☐

 DELTALIGHT®

M20/M26H - SPY 52 TW 96520 DIM5 W

23331 9025 W

Light altering devices



	19810 0010 B HONEYCOMB 42 SINGLE USE B	☐
	19810 0020 LINEAR SPREAD LENS 42	☐
	19810 0030 SPREAD LENS 42	☐
	19810 0040 SOFTENING LENS 42	☐
	19810 0050 GLASS SBL 42	☐
	19810 0060 B HONEYCOMB 42 DOUBLE USE B	☐

M20/M26H - SPY 52 TW 96520 DIM5 W
23331 9025 W

Finish your product



	19810 0100 B SPY 52 TUBE B	☐
	19810 0100 FBR SPY 52 TUBE FBR	☐
	19810 0100 FG SPY 52 TUBE FG	☐
	19810 0100 GC SPY 52 TUBE GC	☐
	19810 0100 W SPY 52 TUBE W	☐

Replaceable reflector / lens

	19810 0180 SPY 52 REFLECTOR 20°	☐
	19810 0190 SPY 52 REFLECTOR 45°	☐
	19810 0240 SPY 52 REFLECTOR 30°	☐

M20/M26H - SPY 52 TW 96520 DIM5 W
23331 9025 W


COMPATIBLE COMPOSABLES

SHIFTLINE M26H + SBL	Available Colours
 30411 9205 SHIFTLINE M26H + SBL 2m DIM5	 
 30411 9305 SHIFTLINE M26H + SBL 2m DIM5	 
 30412 9205 SHIFTLINE M26H + SBL 3m DIM5	 
 30412 9305 SHIFTLINE M26H + SBL 3m DIM5	 
 30413 9205 SHIFTLINE M26H + SBL 4m DIM5	 
 30413 9305 SHIFTLINE M26H + SBL 4m DIM5	 


M20/M26H - SPY 52 TW 96520 DIM5 W
23331 9025 W

SHIFTLINE M26H profile


Available Colours




23359 0000 SLM26H - PROFILE



23359 0010 SLM26H - PROFILE 1m



23359 0020 SLM26H - PROFILE 2m



23359 0030 SLM26H - PROFILE 3m



SPLITLINE M20 ST profile

Available Colours



23397 0000 SPM20 ST - PROFILE







23397 0020 SPM20 ST - PROFILE 2m



23397 0030 SPM20 ST - PROFILE 3m



M20/M26H - SPY 52 TW 96520 DIM5 W
23331 9025 W

SPLITLINE M20 profile		Available Colours
	420 20 10 00 SPM20 - PROFILE 1m	
	420 20 20 00 SPM20 - PROFILE 2m	
	420 20 30 00 SPM20 - PROFILE 3m	
	23301 0000 SPM20 - PROFILE B	

Notes: