





M52 - SPY 52 TW 96520 DIM5 B

24445 9025 B

AVAILABLE IN
BLACK 24445 9025 B
WHITE 24445 9025 W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-20° EXCL.LED POWER SUPPLY 48V-DC DALI DT8 dimming Optional REFLECTORS 30° & 45° available

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	ENEC, LCA

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9W / CRI>90 (R9: 50) / 2700K-6500K / 1087lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1087lm // 9W // 121lm/W
LED TECHNICS (LUMINAIRE)	681lm // 10W // 66lm/W

Remarks

Take a look at our **MAGNETIC PROFILES** movie

Requirements

SPY 52 TUBE
LED POWER SUPPLY 48V-DC

M52 - SPY 52 TW 96520 DIM5 B

24445 9025 B

Accessories

HONEYCOMB 42

SPREAD LENS 42

LINEAR SPREAD LENS 42





SOFTENING LENS 42

GLASS SBL 42

For detailed installation instructions, please consult the manual: [24445_XXX5_HAND.pdf](#)

M52 - SPY 52 TW 96520 DIM5 B
24445 9025 B






FINISH YOUR SPECIFICATION

LED power supplies		#
	300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN	9 ☐
	300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN	23 ☐
	21012 0230 LED POWER SUPPLY 48V-DC / 100W	9 ☐
	21012 0240 LED POWER SUPPLY 48V-DC / 200W	19 ☐

M52 - SPY 52 TW 96520 DIM5 B

24445 9025 B

Light altering devices

	19810 0010 B HONEYCOMB 42 SINGLE USE B	☐
	19810 0020 LINEAR SPREAD LENS 42	☐
	19810 0030 SPREAD LENS 42	☐
	19810 0040 SOFTENING LENS 42	☐
	19810 0050 GLASS SBL 42	☐
	19810 0060 B HONEYCOMB 42 DOUBLE USE B	☐

M52 - SPY 52 TW 96520 DIM5 B

24445 9025 B

Finish your product



19810 0100 B SPY 52 TUBE B

☐

19810 0100 FBR SPY 52 TUBE FBR

☐

19810 0100 FG SPY 52 TUBE FG

☐


19810 0100 GC SPY 52 TUBE GC

☐


19810 0100 W SPY 52 TUBE W

☐


Replaceable reflector / lens



19810 0180 SPY 52 REFLECTOR 20°

☐

19810 0190 SPY 52 REFLECTOR 45°





☐

19810 0240 SPY 52 REFLECTOR 30°

☐

M52 - SPY 52 TW 96520 DIM5 B
 24445 9025 B

COMPATIBLE COMPOSABLES

SPLITLINE M52 profile	Available Colours
 420 52 10 00 SPM52 - PROFILE 1m	
 420 52 20 00 SPM52 - PROFILE 2m	
 420 52 30 00 SPM52 - PROFILE 3m	
 24413 0000 SPM52 - PROFILE	

Notes: