





M26L - SPY 66 TW 96518 DIM5 B

23292 9015 B

AVAILABLE IN
BLACK 23292 9015 B
WHITE 23292 9015 W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.6
ADJUSTABILITY	0° to 90° swiveling, 360° rotatable
INFORMATION	REFLECTOR SP-18° EXCL.LED POWER SUPPLY 48V-DC DALI DT8 dimming Optional REFLECTORS 30° & 45° available

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	ENEC, LCA

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9W / CRI>90 (R9: 50) / 2700K-6500K / 1087lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1087lm // 9W // 121lm/W
LED TECHNICS (LUMINAIRE)	776lm // 10W // 75lm/W

Remarks

Take a look at our **MAGNETIC PROFILES** movie

Requirements

SPY 66 TUBE
 LED POWER SUPPLY 48V-DC

M26L - SPY 66 TW 96518 DIM5 B

23292 9015 B

Accessories

HONEYCOMB 57

SPREAD LENS 57

LINEAR SPREAD LENS 57

SOFTENING LENS 57

GLASS SBL 57

For detailed installation instructions, please consult the manual: [23292_XXX5_HAND.pdf](#)


M26L - SPY 66 TW 96518 DIM5 B

23292 9015 B

FINISH YOUR SPECIFICATION


LED power supplies

#




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

9




300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

23



21012 0230 LED POWER SUPPLY 48V-DC / 100W

9




21012 0240 LED POWER SUPPLY 48V-DC / 200W

19


M26L - SPY 66 TW 96518 DIM5 B

23292 9015 B


Light altering devices




24611 0150 B HONEYCOMB 57 SINGLE USE B




24611 0160 GLASS SBL 57




24611 0170 LINEAR SPREAD LENS 57



24611 0190 SOFTENING LENS 57



24611 0200 SPREAD LENS 57




24611 0210 B HONEYCOMB 57 DOUBLE USE B

M26L - SPY 66 TW 96518 DIM5 B

23292 9015 B

Finish your product



24611 0100 B SPY 66 TUBE B


24611 0100 FBR SPY 66 TUBE FBR

24611 0100 FG SPY 66 TUBE FG

24611 0100 GC SPY 66 TUBE GC

24611 0100 W SPY 66 TUBE W

Replaceable reflector / lens



24611 0220 SPY 66 REFLECTOR 18°



24611 0230 SPY 66 REFLECTOR 30°



24611 0240 SPY 66 REFLECTOR 45°


M26L - SPY 66 TW 96518 DIM5 B

23292 9015 B


COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)


Available Colours




23358 0000 SLM26L - PROFILE



23358 0010 SLM26L - PROFILE 1m



23358 0020 SLM26L - PROFILE 2m



23358 0030 SLM26L - PROFILE 3m



Notes: