





M52 - SPY 66 92718 MDL B

24438 9210 B

AVAILABLE IN
BLACK 24438 9210 B
WHITE 24438 9210 W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.7
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	REFLECTOR SP-18° EXCL.LED POWER SUPPLY 48V-DC Optional REFLECTORS 30° & 45° available

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	E
CERTIFICATES	ENEC, LCA

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 25W / CRI>90 (R9: 60) / 2700K / 2688lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	2688lm // 25W // 108lm/W
LED TECHNICS (LUMINAIRE)	1920lm // 29W // 67lm/W

Remarks

Take a look at our **MAGNETIC PROFILES** movie

Requirements

SPY 66 TUBE
 LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR
 Delta Light NV may revise the information and technical data at any time without notice. Version: 29/11/2024



M52 - SPY 66 92718 MDL B

24438 9210 B

Accessories

HONEYCOMB 57

For detailed installation instructions, please consult the manual: [24438_XXX0_HAND.pdf](#)

M52 - SPY 66 92718 MDL B

24438 9210 B

FINISH YOUR SPECIFICATION

Current supply

#



21032 0030 SMART 48 MODULATOR PLUG-IN WD

6

SMART 48

#



300 90 011 SMART 48 MODULATOR DIM9

6



300 90 012 SMART 48 MODULATOR WD

6


LED power supplies

#



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

3



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

8



21012 0230 LED POWER SUPPLY 48V-DC / 100W

3




21012 0240 LED POWER SUPPLY 48V-DC / 200W

7

M52 - SPY 66 92718 MDL B


24438 9210 B

Light altering devices



24611 0150 B HONEYCOMB 57 SINGLE USE B

Finish your product



24611 0100 B SPY 66 TUBE B

24611 0100 FBR SPY 66 TUBE FBR

24611 0100 FG SPY 66 TUBE FG

24611 0100 GC SPY 66 TUBE GC

24611 0100 W SPY 66 TUBE W

Replaceable reflector / lens



24611 0220 SPY 66 REFLECTOR 18°



24611 0230 SPY 66 REFLECTOR 30°



24611 0240 SPY 66 REFLECTOR 45°


M52 - SPY 66 92718 MDL B

24438 9210 B


COMPATIBLE COMPOSABLES

SPLITLINE M52 profile


Available Colours




420 52 10 00 SPM52 - PROFILE 1m



420 52 20 00 SPM52 - PROFILE 2m



420 52 30 00 SPM52 - PROFILE 3m



24413 0000 SPM52 - PROFILE



Notes: