





SOLI - LINE 60 UP 930 MDL B

27158 9300 B

AVAILABLE IN
BLACK 27158 9300 B
WHITE 27158 9300 W



 [View on website](#)

General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	non adjustable
INFORMATION	EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED flex 11,7W / CRI>90 (R9: 65) / 3000K / 1500lm
SDCM	SDCM3
LM80	L70 > 30000
LED TECHNICS (LIGHT SOURCE)	1500lm // 11,7W // 128lm/W
LED TECHNICS (LUMINAIRE)	995lm // 13W // 74lm/W

Requirements

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual: [27158_XXX0_HAND.pdf](#)


SOLI - LINE 60 UP 930 MDL B

27158 9300 B

FINISH YOUR SPECIFICATION


SMART 48

#



300 90 011 SMART 48 MODULATOR DIM9

14




300 90 012 SMART 48 MODULATOR WD

14


LED power supplies

#




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

7




300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

17



21012 0230 LED POWER SUPPLY 48V-DC / 100W

7



21012 0240 LED POWER SUPPLY 48V-DC / 200W

14


SOLI - LINE 60 UP 930 MDL B

27158 9300 B


COMPATIBLE COMPOSABLES

SOLISCAPE profile

Available Colours



27111 0020 SOLI - PROFILE 2m



27111 0030 SOLI - PROFILE 3m



Notes: