



SPY 39 TRIMLESS 93040 FG

24121 9330 FG

AVAILABLE IN

BLACK 24121 9330 B

BRUSHED ALU 24121 9330 BRA

BRUSHED ANTHRACITE 24121 9330 BRAT

BRUSHED COPPER 24121 9330 BRCU

BRUSHED GOLD 24121 9330 BRG

BRUSHED OLD BRONZE 24121 9330 BROB



FLEMISH BRONZE 24121 9330 FBR

FLEMISH GOLD 24121 9330 FG

GOLD COLOURED 24121 9330 GC

PIANO BLACK 24121 9330 PB

WHITE 24121 9330 W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - Ø KIT
RECESSED DEPTH (MM)	80
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 45° swiveling, 355° rotatable
INFORMATION	REFLECTOR WFL-40° EXCL.LED POWER SUPPLY 350-500mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	D
CERTIFICATES	CB, ENEC

Lightsources info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8-8,6W / CRI>90 (R9: 52) / 3000K / 787-1089lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUPE	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1089lm // 8,6W // 127lm/W
LED TECHNICS (LUMINAIRE)	883lm // 10W // 89lm/W

SPY 39 TRIMLESS 93040 FG

24121 9330 FG

Requirements

SPY 39 TUBE or VISOR 39
MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.
MOUNTING KIT AIR 103
LED POWER SUPPLY 350 / 500mA-DC DIM (Remote)

For detailed installation instructions, please consult the manual: [24121_XXX0_HAND.pdf](#)










CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 System ceiling	 MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.	Required
 Plasterboard	 MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.	Required
 Stucanet	 MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.	Required
 Concrete + plaster	 MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.	Required
 Lintel + plaster	 MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.	Required
 Hollow-core slab + plaster	 MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.	Required
 Stretched ceiling	 MOUNTING KIT SPY 39/52 TRIMLESS CSC	Required
	 MOUNTING KIT SPY 39/52 TRIMLESS WSC	Required
 Ventilation in plasterboard	 MOUNTING KIT SIDE AIR 103	Required
	 MOUNTING KIT NO AIR 103	Required
	 MOUNTING KIT SIDE AIR ONLY 1	Required
 Ventilation in concrete + plaster	 MOUNTING KIT NO AIR 103	Required
	 MOUNTING KIT TOP AIR ONLY 1	Required
	 MOUNTING KIT TOP AIR 103	Required

SPY 39 TRIMLESS 93040 FG











24121 9330 FG

FINISH YOUR SPECIFICATION

LED power supplies			#
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9	1->4(4) / 1->4(4)	☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5	1->2(2) / 1->2(1)	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9	2->6(6) / 1->6(4)	☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7	1->2(2) / 1->2(1)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5	1->2(2) / 1->2(1)	☐
	21012 0010 LED POWER SUPPLY MULTI POWER	1->2 / 1->2	☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1	1->3 / 1->2	☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5	1->3 / 1->2	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL	1->3 / 1->2	☐

SPY 39 TRIMLESS 93040 FG


24121 9330 FG

	21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8	2->2 / 2->2 ☐
	21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8	1 ☐
	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8	2->2 ☐
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8	1->2 / 1->2 ☐
	21012 0308 LED POWER SUPPLY 350mA / 7,35W DIM8	1 ☐
	21012 0318 LED POWER SUPPLY 500mA / 10W DIM8	1 ☐
	21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68	1-2(2) ☐
	21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68	1-2(1) ☐
	21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5	1->2 ☐
	21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5	1->2 ☐

SPY 39 TRIMLESS 93040 FG

24121 9330 FG

Mounting kits




15212 2030

MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.

☐

Mounting kits stretched ceiling



15212 0080

MOUNTING KIT SPY 39/52 TRIMLESS CSC

☐




15212 0160

MOUNTING KIT SPY 39/52 TRIMLESS WSC

☐

Mounting kits side air + light




29810 0030

MOUNTING KIT SIDE AIR 103

☐

Mounting kits top air + light



29810 0230

MOUNTING KIT TOP AIR 103

☐




DELTA LIGHT®

SPY 39 TRIMLESS 93040 FG

24121 9330 FG

Mounting kits side air only




Technical drawing of a mounting kit for side air. It shows a circular base with a central mounting point. Dimensions include a diameter of 100 at the top, a height of 149, and a base diameter of 180. The base is divided into two sections, 180 and 205.

29810 0100 MOUNTING KIT SIDE AIR ONLY 1

☐

Mounting kits top air only




Technical drawing of a mounting kit for top air. It shows a circular base with a central mounting point. Dimensions include a diameter of 125 at the top, a height of 172, and a base diameter of 171. The base is divided into two sections, 171 and 235.

29810 0200 MOUNTING KIT TOP AIR ONLY 1

☐

Mounting kits no air




Technical drawing of a mounting kit for no air. It shows a circular base with a central mounting point. Dimensions include a diameter of 73 at the top, a height of 172, and a base diameter of 180. The base is divided into two sections, 180 and 205.

29810 0070 MOUNTING KIT NO AIR 103

☐

Light altering devices



Technical drawing of a visor. It shows a circular base with a central mounting point. Dimensions include a diameter of 12 at the top and a base diameter of 35.


24144 0030 B VISOR 39 B

☐

SPY 39 TRIMLESS 93040 FG

24121 9330 FG

Finish your product

	<u>24144 0010 B</u>	SPY 39 TUBE B	☐
	<u>24144 0010 FBR</u>	SPY 39 TUBE FBR	☐
	<u>24144 0010 FG</u>	SPY 39 TUBE FG	☐
	<u>24144 0010 GC</u>	SPY 39 TUBE GC	☐
	<u>24144 0010 W</u>	SPY 39 TUBE W	☐
	<u>24144 0070</u>	SPY 39 TUBE SBL	☐

Notes: