



SPY 52 TRIMLESS 93045 B

19811 9330 B

AVAILABLE IN



BLACK 19811 9330 B

FLEMISH BRONZE 19811 9330 FBR

FLEMISH GOLD 19811 9330 FG

GOLD COLOURED 19811 9330 GC

WHITE 19811 9330 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - Ø KIT
RECESSED DEPTH (MM)	80
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° to 45° swiveling, 355° rotatable
INFORMATION	REFLECTOR WFL-45° EXCL. LED POWER SUPPLY 350-700mA-DC Optional REFLECTORS 20° & 30° available

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, LCA

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8-12,4W / CRI>90 (R9: 52) / 3000K / 787-1467lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1467lm // 12,4W // 118lm/W
LED TECHNICS (LUMINAIRE)	939lm // 14W // 66lm/W

Remarks

Max.500mA when using accessories

SPY 52 TRIMLESS 93045 B

19811 9330 B

Requirements

SPY 52 TUBE
MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.
MOUNTING KIT AIR 103
LED POWER SUPPLY 350 / 500 / 700mA-DC DIM (Remote)

Accessories










HONEYCOMB 42
SPREAD LENS 42
LINEAR SPREAD LENS 42
SOFTENING LENS 42
GLASS SBL 42

For detailed installation instructions, please consult the manual: [19811_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 System ceiling	 MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.	Required
 Plasterboard	 MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.	Required
 Stucanet	 MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.	Required
 Concrete + plaster	 MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.	Required
 Lintel + plaster	 MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.	Required
 Hollow-core slab + plaster	 MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.	Required
 Stretched ceiling	 MOUNTING KIT SPY 39/52 TRIMLESS CSC	Required
	 MOUNTING KIT SPY 39/52 TRIMLESS WSC	Required
 Ventilation in plasterboard	 MOUNTING KIT SIDE AIR 103	Required
	 MOUNTING KIT NO AIR 103	Required
	 MOUNTING KIT SIDE AIR ONLY 1	Required
 Ventilation in concrete + plaster	 MOUNTING KIT NO AIR 103	Required
	 MOUNTING KIT TOP AIR ONLY 1	Required
	 MOUNTING KIT TOP AIR 103	Required











FINISH YOUR SPECIFICATION

LED power supplies			#
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9	1->4(4) / 1->4(4) / 1->4(3)	☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5	1->2(2) / 1->2(1) / 1->2(1)	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9	2->6(6) / 1->6(4) / 1->4(3)	☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7	1->2(2) / 1->2(1) / 1(1)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5	1->2(2) / 1->2(1) / 1(1)	☐
	21012 0010 LED POWER SUPPLY MULTI POWER	1->2 / 1->2 / 1->2	☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1	1->3 / 1->2 / 1->2	☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5	1->3 / 1->2 / 1->2	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL	1->3 / 1->2 / 1->2	☐

 DELTALIGHT®


SPY 52 TRIMLESS 93045 B

19811 9330 B

	21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8	2->2 / 2->2 ☐
	21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8	1/1 ☐
	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8	2->2 / 2->2 ☐
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8	1->2 / 1->2 / 1->1 ☐
	21012 0308 LED POWER SUPPLY 350mA / 7,35W DIM8	1 ☐
	21012 0318 LED POWER SUPPLY 500mA / 10W DIM8	1 ☐
	21012 0328 LED POWER SUPPLY 700mA / 15W DIM8	1 ☐
	21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68	1-2(2) ☐
	21012 0490 LED POWER SUPPLY 700mA-DC / 30W IP68	1-2(1) ☐
	21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68	1-2(1) ☐


SPY 52 TRIMLESS 93045 B

19811 9330 B




21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

1->2 ☐



21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5


1->2 ☐



21032 0315 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5

1->2 ☐


Mounting kits



15212 2030 MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.

☐

Mounting kits stretched ceiling



15212 0080 MOUNTING KIT SPY 39/52 TRIMLESS CSC


☐



15212 0160 MOUNTING KIT SPY 39/52 TRIMLESS WSC

☐

Mounting kits side air + light




29810 0030 MOUNTING KIT SIDE AIR 103

☐

SPY 52 TRIMLESS 93045 B

19811 9330 B

Mounting kits top air + light




29810 0230

MOUNTING KIT TOP AIR 103

☐

Mounting kits side air only




29810 0100

MOUNTING KIT SIDE AIR ONLY 1

☐

Mounting kits top air only




29810 0200

MOUNTING KIT TOP AIR ONLY 1

☐

Mounting kits no air



29810 0070

MOUNTING KIT NO AIR 103






☐

 DELTALIGHT®

SPY 52 TRIMLESS 93045 B

19811 9330 B

Light altering devices

	19810 0010 B HONEYCOMB 42 SINGLE USE B	☐
	19810 0020 LINEAR SPREAD LENS 42	☐
	19810 0030 SPREAD LENS 42	☐
	19810 0040 SOFTENING LENS 42	☐
	19810 0050 GLASS SBL 42	☐
	19810 0060 B HONEYCOMB 42 DOUBLE USE B	☐



SPY 52 TRIMLESS 93045 B

19811 9330 B

Finish your product

 40 19810 0100 B SPY 52 TUBE B	☐
19810 0100 FBR SPY 52 TUBE FBR	☐
19810 0100 FG SPY 52 TUBE FG	☐
19810 0100 GC SPY 52 TUBE GC	☐
19810 0100 W SPY 52 TUBE W	☐

Replaceable reflector / lens

 18 19810 0180 SPY 52 REFLECTOR 20°	☐
 18 19810 0190 SPY 52 REFLECTOR 45°	☐
 18 19810 0240 SPY 52 REFLECTOR 30°	☐

Notes: