





SPY 66 TW 96518 ADM DIM5 B

24629 9015 B

AVAILABLE IN
BLACK 24629 9015 B
FULL WHITE 24629 9015 FW
WHITE 24629 9015 W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Mains voltage track Mains voltage track mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.6
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	REFLECTOR SP-18° 3F MULTI DIMMABLE POWER ADAPTER 500mA - (DALI DT8) Optional REFLECTORS 30° & 45° available

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	CB, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9W / CRI>90 (R9: 50) / 2700K-6500K / 1087lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1087lm // 9W // 121lm/W
LED TECHNICS (LUMINAIRE)	776lm // 10W // 75lm/W

Requirements

SPY 66 TUBE
 TRACK 3F DIM



SPY 66 TW 96518 ADM DIM5 B

24629 9015 B

Accessories

HONEYCOMB 57

SPREAD LENS 57

LINEAR SPREAD LENS 57

SOFTENING LENS 57


GLASS SBL 57

For detailed installation instructions, please consult the manual: [24629_XXX5_HAND.pdf](#)

SPY 66 TW 96518 ADM DIM5 B
24629 9015 B

FINISH YOUR SPECIFICATION


Light altering devices




24611 0150 B HONEYCOMB 57 SINGLE USE B

☐


24611 0160 GLASS SBL 57

☐


24611 0170 LINEAR SPREAD LENS 57

☐

24611 0190 SOFTENING LENS 57

☐

24611 0200 SPREAD LENS 57


☐

24611 0210 B HONEYCOMB 57 DOUBLE USE B

☐

SPY 66 TW 96518 ADM DIM5 B
24629 9015 B

Finish your product

	<u>24611 0100 B</u> SPY 66 TUBE B	☐
	<u>24611 0100 FBR</u> SPY 66 TUBE FBR	☐
	<u>24611 0100 FG</u> SPY 66 TUBE FG	☐
	<u>24611 0100 GC</u> SPY 66 TUBE GC	☐
	<u>24611 0100 W</u> SPY 66 TUBE W	☐

Replaceable reflector / lens

	<u>24611 0230</u> SPY 66 REFLECTOR 30°	☐
	<u>24611 0240</u> SPY 66 REFLECTOR 45°	☐

SPY 66 TW 96518 ADM DIM5 B
 24629 9015 B

COMPATIBLE TRACKS

TRACK 3F DIM H			Available Colours
200 14 410	TRACK 3F DIM H 1m	1000 m 1.6 kg	 
200 14 420	TRACK 3F DIM H 2m	2000 m 3.2 kg	 
200 14 430	TRACK 3F DIM H 3m	3000 m 4.8 kg	 
TRACK 3F DIM IN			Available Colours
200 13 410	TRACK 3F DIM IN 1m	1000 m 1.2 kg	 
200 13 420	TRACK 3F DIM IN 2m	2000 m 2.4 kg	 
200 13 430	TRACK 3F DIM IN 3m	3000 m 3.5 kg	 
TRACK 3F DIM ON			Available Colours
200 12 410	TRACK 3F DIM ON 1m	1000 m 1.1 kg	 
200 12 420	TRACK 3F DIM ON 2m	2000 m 2.1 kg	 
200 12 430	TRACK 3F DIM ON 3m	3000 m 3.1 kg	 

Notes: