



SPY 66 CLIP TW 96518 B-B



24622 9010 B-B

AVAILABLE IN

BLACK-BLACK 24622 9010 B-B

FULL WHITE 24622 9010 FW

WHITE-WHITE 24622 9010 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed,Ceiling Surface mounted
CUTOUT SHAPE/SIZE (MM)	round - 51
RECESSED DEPTH (MM)	40
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.6
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	REFLECTOR SP-18° EXCLLED POWER SUPPLY 500mA-DC TW - (DALI DT8) Optional REFLECTORS 30° & 45° available

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, LCA

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9W / CRI>90 (R9: 50) / 2700K-6500K / 1087lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1087lm // 9W // 121lm/W
LED TECHNICS (LUMINAIRE)	776lm // 10W // 75lm/W

Requirements

SPY 66 TUBE

LED POWER SUPPLY 500mA-DC TW

Options

MOUNTING KIT FLUSH SPY

SPY 66 CLIP TW 96518 B-B

24622 9010 B-B

Accessories

- HONEYCOMB 57
- SPREAD LENS 57
- LINEAR SPREAD LENS 57
- SOFTENING LENS 57
- GLASS SBL 57

For detailed installation instructions, please consult the manual: [24622_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY


Ceiling Type	Mounting Kit	
 System ceiling	 MOUNTING KIT FLUSH SPY	Required
 Plasterboard	 MOUNTING KIT FLUSH SPY	Required
 Stucanet	 MOUNTING KIT FLUSH SPY	Required
 Wood	-	
 Concrete	-	
 Concrete + plaster	 MOUNTING KIT FLUSH SPY	Required
 Lintel + plaster	 MOUNTING KIT FLUSH SPY	Required
 Hollow-core slab	-	
 Hollow-core slab + plaster	 MOUNTING KIT FLUSH SPY	Required
 Stretched ceiling	-	

SPY 66 CLIP TW 96518 B-B

24622 9010 B-B

FINISH YOUR SPECIFICATION


LED power supplies #



21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5

1->2 ☐

Mounting kits








414 90 01 MOUNTING KIT FLUSH SPY

☐

SPY 66 CLIP TW 96518 B-B

24622 9010 B-B


Light altering devices

 14 Ø57	24611 0150 B HONEYCOMB 57 SINGLE USE B	☐
 13 Ø57	24611 0160 GLASS SBL 57	☐
 15 Ø57	24611 0170 LINEAR SPREAD LENS 57	☐
 13 Ø57	24611 0190 SOFTENING LENS 57	☐
 14 Ø57	24611 0200 SPREAD LENS 57	☐
 14 Ø57	24611 0210 B HONEYCOMB 57 DOUBLE USE B	☐

SPY 66 CLIP TW 96518 B-B

24622 9010 B-B

Finish your product



24611 0100 B SPY 66 TUBE B

☐

24611 0100 FBR SPY 66 TUBE FBR

☐

24611 0100 FG SPY 66 TUBE FG

☐

24611 0100 GC SPY 66 TUBE GC

☐

24611 0100 W SPY 66 TUBE W

☐

Replaceable reflector / lens



24611 0220 SPY 66 REFLECTOR 18°

☐

24611 0230 SPY 66 REFLECTOR 30°

☐

24611 0240 SPY 66 REFLECTOR 45°

☐

Notes: