





SPY 66 ON TW 96518 B
24624 9010 B

AVAILABLE IN
BLACK 24624 9010 B
FULL WHITE 24624 9010 FW
WHITE 24624 9010 W



 [View on website](#)

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.6
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	REFLECTOR SP-18° EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8) Optional REFLECTORS 30° & 45° available

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, LCA

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9W / CRI>90 (R9: 50) / 2700K-6500K / 1087lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1087lm // 9W // 121lm/W
LED TECHNICS (LUMINAIRE)	776lm // 10W // 75lm/W

Requirements	
SPY 66 TUBE	
LED POWER SUPPLY 500mA-DC TW	

Options	
COVERSET R 90-100	

SPY 66 ON TW 96518 B

24624 9010 B

Accessories

HONEYCOMB 57

SPREAD LENS 57

LINEAR SPREAD LENS 57

SOFTENING LENS 57

GLASS SBL 57

For detailed installation instructions, please consult the manual: [24624_XXX0_HAND.pdf](#)


SPY 66 ON TW 96518 B

24624 9010 B

FINISH YOUR SPECIFICATION

LED power supplies

#




21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5

1->2

☐

Coversets








204 00 100 B COVERSET R 100 B

☐

204 00 100 W COVERSET R 100 W

☐


Light altering devices

	14 24611 0150 B HONEYCOMB 57 SINGLE USE B	☐
	13 24611 0160 GLASS SBL 57	☐
	15 24611 0170 LINEAR SPREAD LENS 57	☐
	13 24611 0190 SOFTENING LENS 57	☐
	14 24611 0200 SPREAD LENS 57	☐
	14 24611 0210 B HONEYCOMB 57 DOUBLE USE B	☐


SPY 66 ON TW 96518 B

24624 9010 B

Finish your product

	24611 0100 B SPY 66 TUBE B	☐
	24611 0100 FBR SPY 66 TUBE FBR	☐
	24611 0100 FG SPY 66 TUBE FG	☐
	24611 0100 GC SPY 66 TUBE GC	☐
	24611 0100 W SPY 66 TUBE W	☐

Replaceable reflector / lens

	24611 0220 SPY 66 REFLECTOR 18°	☐
	24611 0230 SPY 66 REFLECTOR 30°	☐
	24611 0240 SPY 66 REFLECTOR 45°	☐

Notes: