





SPY 90 TW 96518 ADM DIM5 B
19884 9015 B

AVAILABLE IN
BLACK 19884 9015 B
WHITE 19884 9015 W



 [View on website](#)

General info

LOCATION	indoor
INSTALLATION	Mains voltage track Mains voltage track mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	REFLECTOR SP-18° 3F DIMMABLE POWER ADAPTER 500mA-DC - (DALI DT8) Optional REFLECTORS 30° & 45° available

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	F
CERTIFICATES	CB, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 17,8W / CRI>90 (R9: 50) / 2700K-6500K / 2054lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	2054lm // 17,8W // 116lm/W
LED TECHNICS (LUMINAIRE)	1482lm // 20W // 72lm/W

Requirements

SPY 90 TUBE
TRACK 3F DIM

Accessories

HONEYCOMB 75
SPREAD LENS 75
LINEAR SPREAD LENS 75
SOFTENING LENS 75



SPY 90 TW 96518 ADM DIM5 B






19884 9015 B

For detailed installation instructions, please consult the manual: [**19884_XXX5_HAND.pdf**](#)

SPY 90 TW 96518 ADM DIM5 B
 19884 9015 B

FINISH YOUR SPECIFICATION


Light altering devices

 3 19810 0110 B HONEYCOMB 75 SINGLE USE B	☐
 4 19810 0120 B HONEYCOMB 75 DOUBLE USE B	☐
 3 19810 0130 GLASS SBL 75	☐
 3 19810 0140 LINEAR SPREAD LENS 75	☐
 3 19810 0150 SOFTENING LENS 75	☐
 3 19810 0160 SPREAD LENS 75	☐

SPY 90 TW 96518 ADM DIM5 B

19884 9015 B

Finish your product



19810 0170 B SPY 90 TUBE B

☐

19810 0170 DC SPY 90 TUBE DC

☐

19810 0170 FBR SPY 90 TUBE FBR

☐

19810 0170 FG SPY 90 TUBE FG

☐

19810 0170 GC SPY 90 TUBE GC

☐

19810 0170 W SPY 90 TUBE W

☐

Replaceable reflector / lens



19810 0200 SPY 90 REFLECTOR 18°

☐

19810 0210 SPY 90 REFLECTOR 30°

☐

19810 0220 SPY 90 REFLECTOR 45°

☐

COMPATIBLE TRACKS

TRACK 3F DIM H			Available Colours
200 14 410	TRACK 3F DIM H 1m	1000 m 1.6 kg	 
200 14 420	TRACK 3F DIM H 2m	2000 m 3.2 kg	 
200 14 430	TRACK 3F DIM H 3m	3000 m 4.8 kg	 
TRACK 3F DIM IN			Available Colours
200 13 410	TRACK 3F DIM IN 1m	1000 m 1.2 kg	 
200 13 420	TRACK 3F DIM IN 2m	2000 m 2.4 kg	 
200 13 430	TRACK 3F DIM IN 3m	3000 m 3.5 kg	 
TRACK 3F DIM ON			Available Colours
200 12 410	TRACK 3F DIM ON 1m	1000 m 1.1 kg	 
200 12 420	TRACK 3F DIM ON 2m	2000 m 2.1 kg	 
200 12 430	TRACK 3F DIM ON 3m	3000 m 3.1 kg	 

Notes: