





SPY 90 ON 92718 DIM1 B
19882 9211 B

AVAILABLE IN
BLACK 19882 9211 B
FULL WHITE 19882 9211 FW
WHITE 19882 9211 W



 [View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.1
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	REFLECTOR SP-18° INCL.DIMMABLE LED POWER SUPPLY 700mA-DC Optional REFLECTORS 30° & 45° available

Electrical info

ELECTRICAL	120-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	1-10V
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 23,2W / CRI>90 (R9: 60) / 2700K / 3031lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	3031lm // 23,2W // 130lm/W
LED TECHNICS (LUMINAIRE)	2187lm // 27W // 82lm/W

Requirements

SPY 90 TUBE

Accessories

HONEYCOMB 75
SPREAD LENS 75
LINEAR SPREAD LENS 75
SOFTENING LENS 75
CLASS SPY 75



SPY 90 ON 92718 DIM1 B

19882 9211 B


For detailed installation instructions, please consult the manual: [**19882_XXX1_HAND.pdf**](#)

SPY 90 ON 92718 DIM1 B

19882 9211 B

FINISH YOUR SPECIFICATION


Light altering devices




19810 0110 B HONEYCOMB 75 SINGLE USE B

☐

19810 0120 B HONEYCOMB 75 DOUBLE USE B

☐


19810 0130 GLASS SBL 75

☐

19810 0140 LINEAR SPREAD LENS 75

☐

19810 0150 SOFTENING LENS 75

☐

19810 0160 SPREAD LENS 75

☐

SPY 90 ON 92718 DIM1 B

19882 9211 B

Finish your product

	19810 0170 B SPY 90 TUBE B	☐
	19810 0170 DC SPY 90 TUBE DC	☐
	19810 0170 FBR SPY 90 TUBE FBR	☐
	19810 0170 FG SPY 90 TUBE FG	☐
	19810 0170 GC SPY 90 TUBE GC	☐
	19810 0170 W SPY 90 TUBE W	☐

Replaceable reflector / lens

	19810 0200 SPY 90 REFLECTOR 18°	☐
	19810 0210 SPY 90 REFLECTOR 30°	☐
	19810 0220 SPY 90 REFLECTOR 45°	☐

Notes: