





SUPERNOVA LINE 65 DOWN-UP 930 B

20616 9300 B

AVAILABLE IN
BLACK 20616 9300 B
WHITE 20616 9300 W



[View on website](#)

General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	6.4
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL INCL.LED POWER SUPPLY INCL.4 x CABLE SUSPENSION SINGLE AUTO. 3.0m INCL.1 x CABLE 3 x 0.75mm ²

Electrical info	
ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 58,8W / CRI>90 (R9: 50) / 3000K / 8635lm UP: 2 x (LED cluster 7,4W / CRI>90 (R9: 50) / 3000K / 1079lm)
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN: 8635lm // 58,8W // 147lm/W UP: 2158lm // 14,8W // 147lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 6167lm // 68W // 91lm/W UP: 1886lm // 17W // 111lm/W

Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS



SUPERNOVA LINE 65 DOWN-UP 930 B

20616 9300 B


For detailed installation instructions, please consult the manual: [20616_XXX0_HAND.pdf](#)

SUPERNOVA LINE 65 DOWN-UP 930 B

20616 9300 B

FINISH YOUR SPECIFICATION

Current supply


	☐ <u>203 99 55 ANO</u> CABLE BASE R ANO
	☐ <u>203 99 55 B</u> CABLE BASE R B
	☐ <u>203 99 55 W</u> CABLE BASE R W
	☐ <u>203 99 56 ANO</u> CABLE BASE S ANO
	☐ <u>203 99 56 B</u> CABLE BASE S B
	☐ <u>203 99 56 W</u> CABLE BASE S W

Coversets

	☐ <u>204 00 100 B</u> COVERSET R 100 B
	☐ <u>204 00 100 W</u> COVERSET R 100 W

SUPERNOVA LINE 65 DOWN-UP 930 B
20616 9300 B

Suspension parts



328 10 01 SUSPENSION TRIMLESS O.F.A.

☐




15225 0340 B SUSPENSION ST B

☐

15225 0340 W SUSPENSION ST W

☐

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.

☐



15225 0360 B CONNECTION ST B

☐

15225 0360 W CONNECTION ST W

☐

Notes: