



SUPERNOVA LINE 65 TRIMLESS 930

20628 9300



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 685
RECESSED DEPTH (MM)	200
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	7.6
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL INCL.LED POWER SUPPLY

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY INCLUDED	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 58,8W / CRI>90 (R9: 50) / 3000K / 8635lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	8635lm // 58,8W // 147lm/W
LED TECHNICS (LUMINAIRE)	6165lm // 68W // 91lm/W

For detailed installation instructions, please consult the manual: [20628_XXX0_HAND.pdf](#)

SUPERNOVA LINE 65 TRIMLESS 930
 20628 9300

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-

Notes: